
desisim Documentation

Release 0.35.1.dev2193

DESI

Jul 09, 2020

Contents

1 Introduction	1
2 Contents	3
3 Indices and tables	55
Python Module Index	57
Index	59

CHAPTER 1

Introduction

This is the documentation for desisim.

The `toctree` directive can be used to link to other files in this directory and even display their sections. See the [toctree documentation](#).

2.1 Quality Assurance

2.1.1 Overview

The `desisim` package includes a few scripts for running QA on the outputs.

2.1.2 Scripts

`desi_qa_zfind`

Generate redshift accuracy QA based on the truth vs. RedRock outputs.

usage

Here is the usage:

```
usage: desi_qa_zfind [-h] [--verbose] [--load_simz_table LOAD_SIMZ_TABLE]
                   [--reduxdir PATH] [--rawdir PATH] [--yaml_file YAML_FILE]
                   [--qafig_path QAFIG_PATH]
                   [--write_simz_table WRITE_SIMZ_TABLE]
```

Generate QA on redshift for a production [v0.2.1]

optional arguments:

```
-h, --help          show this help message and exit
```

(continues on next page)

(continued from previous page)

```

--verbose          Provide verbose reporting of progress. (default:
                   False)
--load_simz_table LOAD_SIMZ_TABLE
                   Load an existing simz Table to remake figures
                   (default: None)
--reduxdir PATH   Override default path ($DESI_SPECTRO_REDUX/$SPECPROD)
                   to processed data. (default: None)
--rawdir PATH     Override default path ($DESI_SPECTRO_REDUX/$SPECPROD)
                   to processed data. (default: None)
--yaml_file YAML_FILE
                   YAML file for debugging (primarily). (default: None)
--qafig_path QAFIG_PATH
                   Path to where QA figure files are generated. Default
                   is specprod_dir+/QA (default: None)
--write_simz_table WRITE_SIMZ_TABLE
                   Write simz to this filename (default: None)

```

example

Here is the typical execution:

```
desi_qa_zfind
```

desi_qa_s2n

Generate S/N QA for all object types for all of the nights in a production. The object types and redshifts are taken from *truth*.

usage

Here is the usage:

```

usage: desi_qa_s2n [-h] [--reduxdir PATH] [--qafig_path QAFIG_PATH]

Generate S/N QA for a production [v0.2.1]

optional arguments:
  -h, --help          show this help message and exit
  --reduxdir PATH     Override default path ($DESI_SPECTRO_REDUX) to
                       processed data. (default: None)
  --qafig_path QAFIG_PATH
                       Path to where QA figure files are generated. Default
                       is specprod_dir+/QA (default: None)

```

examples

Generate the figures:

```
desi_qa_s2n
```

A series of PNG files are created for the various cameras and object types.

2.2 desisim change log

2.2.1 0.35.2 (unreleased)

- New keyword in quickcat to indicate which HDU to read in fba files (PR #538)
- Fix sky level Travis test failure (#534) and “low QSO flux” template unit test failure (#507) (PR #536).
- Add freeze_iers to more functions in simexp (direct to master).
- Add the option to run quickquasars in eBOSS mode (PR #481)

2.2.2 0.35.1 (2020-04-15)

- Add freeze_iers to quickgen (direct fix to master).

2.2.3 0.35.0 (2020-04-13)

- Use desiutil.iers.freeze_iers instead of desisurvey (requires desiutil >= 2.0.3) (PR #530).
- Update BAL_META columns (PR #527).

2.2.4 0.34.3 (2020-04-07)

- Add functionality to simulate transients into galaxy spectra; includes several example notebooks (PR #525).
- Added a new table with a development emission line table (PR #523).

2.2.5 0.34.2 (2019-12-27)

- Add `desisurvey.utils.freeze_iers()` to any code that uses `astropy.time` (PR #520).

2.2.6 0.34.1 (2019-12-20)

- New fiberassign file names (PR #519).
- Minor change to DLA metadata (PR #517).
- Use `desitarget.io.find_target_files` to find (mock) target catalogs (PR #514).
- Update `desisim.module` to use latest v3.2 basis templates (PR #513).

2.2.7 0.34.0 (2019-10-17)

Requires desispec/0.30.0 or later.

- Support mocks in bright/dark subdirs (PR #508).
- Support FIBERASSIGN_X/Y instead of DESIGN_X/Y from fiberassign (PR #512).

2.2.8 0.33.1 (2019-10-01)

- *No code or API changes in this tag.*
- Pinned Numpy version to fix broken tests (PR #505).
- Minor changes to documentation configuration and docstrings.

2.2.9 0.33.0 (2019-09-30)

- Running quickquasar on recent London mocks (PR #495, PR #497).
- Update eBOSS to DR16 (PR #498).
- Updates to pixsim for SV (PR #502).
- Fix bug in counting repeat observations (PR #503).

2.2.10 0.32.0 (2019-05-30)

- LyA/QSO sims updates (PR #471, PR #472, PR #473, PR #475, PR #478, PR #483, PR #485, PR #488)
- Misc cleanup (PR #480, PR #479,
- Support new tile naming in quicksurvey (PR #486).
- Fix crashing bug in mock spectra OBJMETA tracking (PR #490).
- Support SV1_DESI_TARGET (PR #494).

2.2.11 0.31.2 (2019-02-28)

- Update quickquasars default redshift error (PR #466).
- Support for London mocks v5.0 + DLAs (PR #467).

2.2.12 0.31.1 (2018-12-14)

- quickquasars updates:
 - support eBOSS (PR #450).
 - mimic redshift fitter uncertainties (PR #452).
 - adding shift to redshift (PR #454).
 - fix error in size of Z_noFOG (PR #455).
 - Fix quickquasars targetid truth (PR #457).
- Precompute colors for star and galaxy templates. (PR #453).
- Refactor S/N qa to load cframes only once (also updates OII for new TRUTH table) (PR #459, PR #465).
- Use basis_templates v3.1 and matching desisim-testdata 0.6.1 (PR #464).

2.2.13 0.31.0 (2018-11-08)

- Update to new fibermap format for consistency with targeting and fiber assignment; requires desispec \geq 0.26.0 (PR #446).
- Update *desisim.templates.BGS* to use latest selection cuts (PR #439).
- Fix quickquasar to work with Saclay mocks (PR #435).
- Add support for $>$ v3.0 stellar templates, with notebook to boot (PR #434).
- Update notebook describing the construction of the LRG templates (PR #433).
- Fix quicksurvey (PR #431).
- Update quickcat model (PR #430, PR #427).
- Fix archetype computation for redrock (PR #429).
- Change `electron` to `count` for FITS compliance (PR #428).
- Do not include Mg II emission by default (PR #426).
- Add and adjust the nebular emission line spectra added to galaxy templates (PR #424).
- quickquasar options for random z, ignoring transmission, random seeds, *desisim.templates.SIMQSO* vs. *QSO* (PR #419, PR #408, PR #406, PR #401).
- Read and write *select_mock_targets* style *simspec* file (PR #416).
- Restore *quickquasars* to a functioning state, after being broken in PR #409 (PR #413).
- Add optional *nside* and *overwrite* arguments to *wrap-newexp* and *obs.new_exposure*, respectively (PR #412).
- Major (and backwards-incompatible) refactor of how the template/simulated metadata are returned by *desisim.templates* (PR #409).
- Adding reading metals from LyA transmission files (PR #407).

2.2.14 0.30.0 (2018-08-09)

- Update templates to DR7+ standard-star designation (FSTD \rightarrow STD) (PR #400).
- Update standard star bit name again STD \rightarrow STD_FAINT; requires desitarget 0.23.0 (PR #402).

2.2.15 0.29.0 (2018-07-26)

- Option in quickspectra to write the full sim table (PR #392).
- Option to use Gaussian instead of Poisson for QSO DLA. Requires *specsim* \geq v0.12 (PR #393).
- Use *overwrite* instead of *clobber* for *astropy.io.fits* (PR #395).

2.2.16 0.28.0 (2018-07-18)

- Add BALs to *templates.QSO* class (PR #321).
- Enable redshift QA using input summary catalogs of truth and redshifts (PR #349).
- Add *zstats*-like good/fail/miss/list QA method from *desitest* mini notebook and refactor previous code to enable it (PR #351).

- quickquasar mags and random seed (PR #350 and PR #352).
- New pixsim and pixsim_nights (PR #353, PR #354, and PR #358).
- Generate confusion matrix related to Spectype (PR #359).
- Update QA to use qaproduct_dir
- Fix newexp-mock wrapper when first expid != 0 (PR #361).
- newexp-mock options for production running (PR #363).
- Add BALs to QSO spectra outside of desisim.templates (PR #370).
- Add rest-frame option to templates.SIMQSO (PR #377).
- Optionally change output wave vector in templates.SIMQSO when noresample=True or restframe=True (PR #383).
- Fix newexp-mock and wrap-fastframe file parsing for NIGHT/EXPID/*. * vs. NIGHT/*. *.
- Speed up emission line simulation when using MKL >= 2018.0.2 (PR #390).

2.2.17 0.27.0 (2018-03-29)

- Fix pixsim_mpi; make it faster with scatter/gather (PR #329, PR #332, and PR #344).
- Fix PSF convolution for newexp-mock (PR #331).
- BGS redshift bug fix (PR #333).
- Astropy 2 compatibility (PR #334).
- Fix newexp-mock -nspec option (PR #340).
- Fix fibermap EXTNAME (PR #340).
- Fix PSF convolution for newexp_mock (PR #331).
- Match desispec renaming and relocating of of pix -> preproc (PR #337 and PR #339).
- More robust handling of unassigned fiber inputs (PR #341).

2.2.18 0.26.0 (2018-02-27)

Requires desitarget >= 0.19.0

- Update BGS fiber acceptance vs. z (PR #326)
- Update desitarget imports for desitarget/0.19.0 (PR #328)

2.2.19 0.25.1 (2018-02-23)

Requires desitarget < 0.19.0

- Fix set_xscales(...) nonposy -> nonposx for qa_zfind

2.2.20 0.25.0 (2018-02-23)

- Fix double PSF convolution in pixsims (PR #320).
- Additional edits to QA scripts and doc to run with mini Notebook (PR #322).
- Optional specsconfig for simulating spectra (PR #325)

2.2.21 0.24.0 (2018-01-30)

- Support new LRG templates (v2.0). (PR #302).
- Bug fixes and additional features added to SIMQSO template maker. (PR #303).
- Fixes quickspectra (broken by desispec change) (PR #306).
- Fixes quickspectra random seed (never worked?) (PR #306).
- Improves pixsim_mpi performance (PR #312).
- Optionally do not wavelength resample simqso templates (PR #310).
- Default to basis templates v2.4 instead of 2.3
- Minor edits to QA scripts and doc (PR #311).
- Adds quickspectra `-skyerr` option (PR #313).
- Correct fastframe output BUNIT (PR #317).

2.2.22 0.23.0 (2017-12-20)

- Fixed crash in newexp-mock success print message.
- Refactor DLA code into its own module (PR #294).
- Adds reader for LyA skewer v2.x format (PR #297).
- Removed deprecated brick output from quickgen.
- Preliminary support for simqso based QSO templates (PR #293).
- fastframe can directly output cframes (PR #287).
- adds BGS efficiency notebooks (PR #285 and PR #286).

2.2.23 0.22.0 (2017-11-10)

- Scaling updates to wrap-fastframe and wrap-newexp (PR #274).
- Fix a minor units scaling bug in lya_spectra (PR #264).
- newexp takes exposures list with EXPID and arcs/flats (PR #275).
- lyman alpha QSOs with optional DLAs (PR #275).
- Update arc lamp line list (PR #272).
- Fix MPI pixsim wrappers (PR #265 and PR #262).
- quicksurvey updates for latest surveysim outputs (PR #270).
- Adds fastfiber method of fiber input loss calculations (PR #261).

- Fix quickgen moon input parameters (PR #263).
- Adds quickspectra script (PR #259).

2.2.24 0.21.0 (2017-09-29)

- Major refactor of newexp to add connection to upstream mocks, surveysims, and fiber assignment (PR #250).
- Support latest (>DR4) data model in the templates metadata table and also scale simulated templates by $1e17$ erg/s/cm²/Angstrom (PR #252).
- Add desi_qa_s2n script (PR #254)
- Refactor desi_qa_zfind script (PR #254)
- Refactor redshift QA for new data model (PR #254)
- Refactor shared QA methods to desisim.spec_qa.utils (PR #254)
- New plots for S/N of spectra for various objects (ELG, LRG, QSO) (PR #254)
- Add BGS, MWS to z_find QA
- Miscellaneous polishing in QA (velocity, clip before RMS, extend [OII] flux, S/N per Ang)
- Bug fix: correctly select both “bright” and “faint” BGS templates by default (PR #257).
- Updates for newexp/fastframe wrappers for end-to-end sims (PR #258).

2.2.25 0.20.0 (2017-07-12)

- Adds tutorial on simulating spectra (PR #244).
- Fixes QSO template wavelength extrapolation (PR #247); requires desispec > 0.15.1.
- Uses `desitarget.cuts.isLRG_colors`; requires `desitarget` >= 0.14.0 (PR #246).
- Uses `desiutil.log` instead of `desispec.log`.

2.2.26 0.19.0 (2017-06-15)

- “FLAVOR” keyword is arc/flat/science but not dark/bright/bgs/mws/etc to match desispec usage (PR #243).
- Add `nocolorcuts` option for LyA spectra (PR #242).
- Fixes for `targets.dat` to `targets.yaml` change (PR #240).
- Changed refs to `desispec.brick` to its new location at `desiutil.brick` (PR #241).
- Remove LyA absorption below the LyA limit (PR #236).
- Refactor and speed-up of QSO templates; add LyA forest on-the-fly (PR #234).

2.2.27 0.18.3 (2017-04-13)

- Add DLAs to lya spectra (PR #220)
- Fix quickgen for specsims v0.8 (PR #226).
- Add verbose output to templates code (PR #230).

- Much faster quickcat (PR #233).

2.2.28 0.18.2 (2017-03-27)

- Fixed a number of documentation errors (PR #224).
- Removed unneeded Travis scripts in `etc/`.
- Fixed N^2 scaling of `desisim.templates.QSO.make_templates()`.
- Speed up `desisim.templates.GALAXY` by factor of 8-12 by caching velocity dispersions (PR #229)

2.2.29 0.18.1 (2016-03-05)

- Update `desisim.module` to use `DESI_BASIS_TEMPLATES v2.3`.

2.2.30 0.18.0 (2016-03-04)

- `pixsims` add new required keywords `DOSVER`, `FEEVER`, `DETECTOR`.
- Small bug fixes in quickcat; drop unused `truth`, `targets` columns to save memory in quicksurvey loop (PRs #198, #199).
- quickgen update to support white dwarf templates (PR #204)
- several enhancements of the templates code
 - optionally output rest-frame templates (PR #208)
 - rewrite of `lya_spectra` to achieve factor of 10 speedup; use `COSMO` (`astropy.cosmology setup`) as a new optional keyword for `qso_desi_templates`; updated API (PRs #210, #212)
 - various small changes to `desisim.templates` (PR #211)
 - support for DA and DB white dwarf subtypes (PR #213)
- update test dependencies (PR #214)

2.2.31 0.17.1 (2016-12-05)

- Fix bug when obsconditions contain tiles that don't overlap catalog
- Add `surveysim --start_epoch` option

2.2.32 0.17.0 (2016-12-02)

- fixes tests for use with latest `desitarget` master
- Refactor quickgen and quickbrick to reduce duplicated code (PR #184)
- Makes BGS compatible with `desitarget` master after `isBGS` -> `isBGS_faint` vs. `isBGS_bright`
- Refactor quickcat to include dependency on observing conditions
- Update quicksurvey to use observing conditions from `surveysim`
- Fixes use of previous `zcatalog` when updating catalog with new observations

2.2.33 0.16.0 (2016-11-10)

- Requires specsim \geq v0.6
- Add integration test for quickgen (PR #179)
- Cache specsim Simulator for faster testing (PR #178)
- Add `lya_spectra.get_spectra` (PR #156)
- Add quickgen and quickbrick unit tests and bug fixes (PR #176, #177)

2.2.34 0.15.0 (2016-10-14)

- Fix some `build_sphinx` errors.
- Run coverage tests under Python 2.7 for now.
- Update template Module file to new DESI+Anaconda infrastructure.
- quickbrick unit tests and bug fixes (#166)
- new quickgen features (PR #173 and #175)
 - fix `exptime` and `airmass` for specsim v0.5
 - new `-frameonly` option
 - moon phase, angle, and zenith options
 - misc cleanup and unit tests

2.2.35 0.14.0 (2016-09-14)

- updates for python 3.5

2.2.36 0.13.1 (2016-08-18)

- fix `batch.pixsim` seeds vs. seed typo

2.2.37 0.13.0 (2016-08-18)

- `desi_qa_zfind`: fixed `-reduxdir` option; improved plots
- PR#132: major refactor of template generation, including ability to give input redshifts, magnitudes, or random seeds from metadata table.
- `desisim.batch.pixsim` functions propagate random seeds for reproducibility

2.2.38 0.12.0 (2016-07-14)

- `desi_qa_zfind` options to override raw and processed data directories
- `PRODNAME` -> `SPECPROD` and `TYPE` -> `SPECTYPE` to match latest `desispec`
- remove unused `get_simstds.py`
- fix #142 so that `pixsim` only optionally runs preprocessing

- fix #141 to avoid repeated TARGETIDs when simulating both bright and dark tiles together
- add `io.load_simspec_summary()` convenience function to load and merge truth information from fibermap and simspec files.
- adjusts which magnitudes were plotted for each target class

2.2.39 0.11.0 (2016-07-12)

Pixsim updates:

- simulate fully raw data, then call preprocessing
- bug fix for simulating tiles in parallel
- fix pixsim loading of non-default PSFs

2.2.40 0.10.0 and prior

- No changes.rst yet

2.3 desisim API

2.3.1 desisim

Tools for DESI instrument simulations, including input templates. It does not cover cosmology simulations.

2.3.2 desisim.archetypes

Archetype routines for desisim.

class `desisim.archetypes.ArcheTypes` (*chi2*)

Object for generating archetypes and determining their responsibility.

Parameters `chi2` (*numpy.ndarray*) – Chi² matrix computed by `desisim.archetypes.compute_chi2()`.

get_archetypes (*chi2_thresh=0.1, responsibility=False*)

Solve the SCP problem to get the final set of archetypes and, optionally, their responsibility.

Note: We assume that each template has uniform “cost” but a more general model in principle could be used / implemented.

Parameters

- **chi2** (*numpy.ndarray*) – Chi² matrix computed by `archetypes.compute_chi2()`.
- **chi2_thresh** (*float*) – Threshold chi2 value to differentiate “different” templates.
- **responsibility** (*bool*) – If True, then compute and return the responsibility of each archetype.

Returns

- If *responsibility==True* then returns a tuple of (*iarch, resp, respindx*) where –
iarch [integer numpy.array] Indices of the archetypes [N].

resp [integer numpy.array] Responsibility of each archetype [N].

respindx [list of] Indices the parent sample each archetype is responsible for [N].

- *If responsibility==False then only iarch is returned.*

responsibility (*iarch, a_matrix*)

Method to determine the responsibility of each archetype.

In essence, the responsibility is the number of templates described by each archetype.

Parameters

- **iarch** (*indices of the archetypes*)–
- **a_matrix** (*distance matrix*)–

Returns

- **resp** (*responsibility of each archetype (number of objects represented by each archetype)*)
- **respindx** (*list containing the indices of the parent objects represented by each archetype*)

`desisim.archetypes.compute_chi2` (*flux, ferr=None*)

Compute the chi2 distance matrix.

Parameters

- **flux** (*numpy.ndarray*) – Array [Nspec, Npix] of spectra or templates where Nspec is the number of spectra and Npix is the number of pixels.
- **ferr** (*numpy.ndarray*) – Uncertainty spectra corresponding to flux (default None).

Returns

chi2 [numpy.ndarray] Chi² matrix [Nspec, Nspec] between all combinations of normalized spectra.

amp [numpy.ndarray] Amplitude matrix [Nspec, Nspec] between all combinations of spectra.

Return type Tuple of (chi2, amp) where

2.3.3 desisim.bal

Functions and methods for inserting BALs into QSO spectra.

class `desisim.bal.BAL`

Base class for inserting BALs into (input) QSO spectra.

empty_balmeta (*qsoredshift=None*)

Initialize an empty metadata table for BALs.

insert_bals (*qsowave, qsoflux, qsoredshift, balprob=0.12, seed=None, verbose=False, qsoid=None*)

Probabilistically inserts BALs into one or more QSO spectra.

Parameters

- **qsowave** (*numpy.ndarray*) – observed-frame wavelength array [Angstrom]
- **qsoflux** (*numpy.ndarray*) – array of observed frame flux values.
- **qsoredshift** (*numpy.array or float*) – QSO redshift
- **balprob** (*float, optional*) – Probability that a QSO is a BAL (default 0.12). Only used if QSO(balqso=True) at instantiation.
- **seed** (*int, optional*) – input seed for the random numbers.

- **verbose** (*bool, optional*) – Be verbose!

Returns QSO spectrum with the BAL included. `balmeta` (`astropy.Table`): metadata table for each BAL.

Return type `bal_qsoflux` (`numpy.ndarray`)

template_balmeta (*indx*)

Initialize an empty metadata table for BALs.

2.3.4 desisim.batch

Batch scripts. Why exactly is this sub-package different from `desisim.scripts`?

`desisim.batch.calc_nodes` (*ntasks, tasktime, maxtime*)

Return a recommended number of nodes to use to process *ntasks* within *maxtime* if each one takes *tasktime* minutes.

2.3.5 desisim.cosmology

All cosmology related routines of desisim should be put here for consistency.

2.3.6 desisim.dla

Functions and methods for inserting DLAs into QSO spectra.

`desisim.dla.calc_lz` (*z, boost=1.6*)

Parameters

- **z** (*ndarray*) – redshift values for evaluation
- **boost** (*float*) – boost for SLLS (should be 1 if only running DLAs)

Returns $l(z)$ aka dN/dz values of DLAs

Return type `ndarray`

`desisim.dla.calculate_lox` (*model, NHI_min, NHI_max=None, neval=10000, cumul=False*)

Calculate $l(X)$ over an `N_HI` interval

Parameters

- **z** (*float*) – Redshift for evaluation
- **NHI_min** (*float*) – minimum log NHI value
- **NHI_max** (*float, optional*) – maximum log NHI value for evaluation (Infinity)
- **neval** (*int, optional*) – Discretization parameter (10000)
- **cumul** (*bool, optional*) – Return a cumulative array? (False)
- **cosmo** (*astropy.cosmology, optional*) – Cosmological model to adopt (as needed)

Returns `IX` – $l(X)$ value

Return type `float`

`desisim.dla.dla_spec` (*wave, dlas*)

Generate spectrum absorbed by dlas :param wave: observed wavelengths :type wave: ndarray :param dlas: DLA dict's :type dlas: list

Returns ndarray of absorbed flux

Return type abs_flux

`desisim.dla.evaluate_fn` (*model, NHI*)

Evaluate an f(N,X) model at a set of NHI values

Parameters **NHI** (*array*) – log NHI values

Returns log_fn – f(NHI,X) values

Return type array

`desisim.dla.init_fNHI` (*slls=False, mix=True*)

Parameters

- **slls** (*bool*) – SLLS only?
- **mix** (*bool*) – Mix of DLAs and SLLS?

Returns fNHI model

Return type model

`desisim.dla.insert_dlas` (*wave, zem, rstate=None, seed=None, fNHI=None, debug=False, **kwargs*)

Insert zero, one or more DLAs into a given spectrum towards a source with a given redshift :param wave: wavelength array in Ang :type wave: ndarray :param zem: quasar emission redshift :type zem: float :param rstate: for random numberes :type rstate: numpy.random.rstate, optional :param seed: :type seed: int, optional :param fNHI: f_NHI object :type fNHI: spline :param **kwargs: Passed to init_fNHI()

Returns List of DLA dict's with keys z,N dla_model (ndarray): normalized spectrum with DLAs inserted

Return type dlas (list)

`desisim.dla.voigt_tau` (*wave, par*)

Find the optical depth at input wavelengths Taken from linetools.analysis.voigt

This is a stripped down routine for calculating a tau array for an input line. Built for speed, not utility nor with much error checking. Use wisely. And take careful note of the expected units of the inputs (cgs)

Parameters

- **wave** (*ndarray*) – Assumed to be in cm
- **parm** (*list*) –

Line parameters. All are input unitless and should be in cgs par[0] = logN (cm⁻²)
par[1] = z par[2] = b in cm/s par[3] = wrest in cm par[4] = f value par[5] = gamma (s⁻¹)

Returns tau – Optical depth at input wavelengths

Return type ndarray

`desisim.dla.voigt_wofz` (*vin, a*)

Uses scipy function for calculation. Taken from linetools.analysis.voigt

Parameters

- **vin** (*ndarray*) – u parameter

- **a** (*float*) – a parameter

Returns `voigt`

Return type `ndarray`

2.3.7 desisim.eboss

Functions and methods for mimicking eBOSS survey.

class `desisim.eboss.FootprintEBOSS` (*nside=16*)

Class to store eBOSS footprint and provide useful functions.

class `desisim.eboss.RedshiftDistributionEBOSS` (*dz=0.04, nside=16*)

Class to store eBOSS redshift distribution fraction to DESI redshift distribution and provide useful functions.

static read_sdss_redshift_distribution (*dz, nside*)

Read the SDSS redshift fraction ascii file

Parameters

- **dz** (*float*) – Step in redshift
- **nside** (*int*) – NSIDE for the sky

Returns redshift fraction histogram dictionary

Return type `hist (dic)`

redshift_fraction (*ra, dec, z*)

Get the associated fraction for randoms at a given redshift slice

Parameters

- **ra** (*float, array of float*) – Right Ascension
- **dec** (*float, array of float*) – Declination
- **z** (*float, array of float*) – redshift

Returns fraction to use to select randoms

Return type `fraction (float, array of float)`

`desisim.eboss.create_sdss2desi_redshift_distribution_ratio` (*sdss_cat, desi_cat, out, dz=0.04, mjd_min=55000, nside=16, nest=True, zminDensity=1.8, densityCut=30.0*)

Create an ascii file giving the subsample fraction as a function of redshift to get the same redshift distribution in DESI as in SDSS

Parameters

- **sdss_cat** (*path*) – Input SDSS quasar catalog
- **desi_cat** (*path*) – Input DESI quasar catalog
- **out** (*path*) – Output ascii file
- **dz** (*float*) – Step in redshift (default=0.04)
- **mjd_min** (*int*) – Minimum MJD (default=55000)

- **nside** (*int*) – NSIDE for the sky (default==16)
- **nest** (*bool*) – NEST for the sky (default==True)
- **zminDensity** (*float*) – Redshift minimum cut to compute the density (default=1.8)
- **densityCut** (*float*) – Density criterium for low vs. high (default=30.)

Returns None

`desisim.eboss.create_sdss_footprint` (*sdss_cat*, *out*, *mjd_min=55000*, *zmin=1.8*, *nside=16*,
nest=True)

Create an ascii file giving for each HEALPix index the density of quasars in number per square degree

Parameters

- **sdss_cat** (*path*) – Input SDSS quasar catalog
- **out** (*path*) – Output ascii file
- **mjd_min** (*int*) – Minimum MJD (default=55000)
- **zmin** (*float*) – Minimum redshift (default==1.8)
- **nside** (*int*) – NSIDE for the sky (default==16)
- **nest** (*bool*) – NEST for the sky (default==True)

Returns None

`desisim.eboss.sdss_subsample` (*ra*, *dec*, *input_highz_density*, *eboss_footprint*)

Downsample input list of angular positions based on SDSS footprint and input density of all quasars .

Parameters

- **ra** (*ndarray*) – Right ascension (degrees)
- **dec** (*ndarray*) – Declination (degrees)
- **input_highz_density** (*float*) – Input density of all quasars per sq.deg.

Returns mask to apply to downsample input list

Return type selection (ndarray)

`desisim.eboss.sdss_subsample_redshift` (*ra*, *dec*, *z*, *eboss_redshift*)

Get the array of selection to get the redshift distribution of SDSS

Parameters

- **ra** (*float*, *array of float*) – Right Ascension
- **dec** (*float*, *array of float*) – Declination
- **z** (*array of float*) – redshift

Returns Array for selection

Return type selection (array of bool)

2.3.8 desisim.io

I/O routines for desisim

class `desisim.io.SimSpec` (*flavor, wave, flux, skyflux, fibermap, truth, obsconditions, header, objtruth=None*)

Lightweight wrapper object for simspec data

Object has properties `flavor, nspec, wave, flux, skyflux, fibermap, truth, obsconditions, header, cameras`.

`cameras` is dict, keyed by camera name, of `SimSpecCameras` objects with properties `wave, phot, skyphot`.

add_camera (*camera, wave, phot, skyphot=None*)

Add per-camera photons to this `SimSpec` object, using `SimSpecCamera`

Parameters

- **camera** – camera name, e.g. `b0, r1, z9`
- **wave** – 1D[nwave] array of wavelengths
- **phot** – 2D[nspec, nwave] array of photons per bin (not per Angstrom)

Optional: `skyphot`: 2D[nspec, nwave] array of sky photons per bin

class `desisim.io.SimSpecCamera` (*camera, wave, phot, skyphot=None*)

Wrapper of per-camera photon data from a simspec file

`desisim.io._parse_filename` (*filename*)

Parse filename and return (prefix, camera, expid)

`camera=None` if the filename isn't camera specific

e.g. `/blat/foo/simspec-00000003.fits` -> ('simspec', None, 3) e.g. `/blat/foo/preproc-r2-00000003.fits` -> ('preproc', 'r2', 3)

`desisim.io._qso_format_version` (*filename*)

Return 1 or 2 depending upon QSO basis template file structure

`desisim.io._resize` (*image, shape*)

Resize input image to have new shape, preserving its 2D arrangement

Parameters

- **image** – 2D ndarray
- **shape** – tuple (ny,nx) for desired output shape

Returns new image with `image.shape == shape`

`desisim.io.empty_metatable` (*nmodel=1, objtype='ELG', subtype="", simqso=False, input_meta=False*)

Initialize template metadata tables depending on the given object type.

Parameters

- **nmodel** (*int*) – Number of rows in output table. Defaults to 1.
- **objtype** (*str*) – Object type. Defaults to ELG.
- **subtype** (*str*) – Subtype for the given object type (e.g., LYA is `objtype=QSO`). Defaults to `.`
- **simqso** (*bool*) – Initialize a templates.SIMQSO-style objmeta table rather than a templates.QSO one. Defaults to False.

- **input_meta** (`bool`) – Initialize an `input_meta` table for use with the various `desisim.templates` classes (see its use in, e.g., `desitarget.mock.mockmaker`) Defaults to `False`.

Returns

- **meta** (`astropy.table.Table`) – Metadata table which is agnostic about the object type.
- **objmeta** (`astropy.table.Table`) – Objtype-specific supplemental metadata table (e.g., containing the [OII] flux for ELG targets and surface gravity for stars).

`desisim.io.empty_snetatable(nmodel=1)`

Initialize a metadata table for SNE.

Parameters `nmodel` (`int`) – Number of rows in output table. Defaults to 1.

Returns `snetmeta` – Metadata table.

Return type `astropy.table.Table`

`desisim.io.fibers2cameras(fibers)`

Return a list of cameras covered by an input array of fiber IDs

`desisim.io.find_basis_template(objtype, indir=None)`

Return the most recent template in `$DESI_BASIS_TEMPLATE/{objtype}_template*.fits`

`desisim.io.find_cosmics(camera, exptime=1000, cosmics_dir=None)`

Return full path to cosmics template file to use

Parameters

- **camera** (`str`) – e.g. ‘b0’, ‘r1’, ‘z9’
- **exptime** (`int`, *optional*) – exposure time in seconds
- **cosmics_dir** (`str`, *optional*) – directory to look for cosmics templates; defaults to `$DESI_COSMICS_TEMPLATES` if set or otherwise `$DESI_ROOT/spectro/templates/cosmics/v0.3` (note `HARDCODED` version)

Exposure times <120 sec will use the bias templates; otherwise they will use the dark cosmics templates

`desisim.io.findfile(filetype, night, expid, camera=None, outdir=None, mkdir=True)`

Return canonical location of where a file should be on disk

Parameters

- **filetype** (`str`) – file type, e.g. ‘preproc’ or ‘simpix’
- **night** (`str`) – YEARMDD string
- **expid** (`int`) – exposure id integer
- **camera** (`str`) – e.g. ‘b0’, ‘r1’, ‘z9’
- **outdir** (*Optional*[`str`]) – output directory; defaults to `$DESI_SPECTRO_SIM/$PIXPROD`
- **mkdir** (*Optional*[`bool`]) – create output directory if needed; default `True`

Returns full file path to output file

Return type `str`

Also see `desispec.io.findfile()` which has equivalent functionality for real data files; this function is only for simulation files.

`desisim.io.get_tile_radec` (*tileid*)

Return (ra, dec) in degrees for the requested tileid.

If tileid is not in DESI, return (0.0, 0.0) TODO: should it raise an exception instead?

`desisim.io.load_simspec_summary` (*indir*, *verbose=False*)

Combine fibermap and simspec files under indir into single truth catalog

Parameters *indir* – path to input directory; search this and all subdirectories

Returns `astropy.table.Table` with true Z catalog

`desisim.io.read_basis_templates` (*objtype*, *subtype=""*, *outwave=None*, *nspec=None*, *infile=None*, *onlymeta=False*, *verbose=False*)

Return the basis (continuum) templates for a given object type. Optionally returns a randomly selected subset of nspec spectra sampled at wavelengths outwave.

Parameters

- **objtype** (*str*) – object type to read (e.g., ELG, LRG, QSO, STAR, STD, WD, MWS_STAR, BGS).
- **subtype** (*str*, *optional*) – template subtype, currently only for white dwarfs. The choices are DA and DB and the default is to read both types.
- **outwave** (*numpy.array*, *optional*) – array of wavelength at which to sample the spectra.
- **nspec** (*int*, *optional*) – number of templates to return
- **infile** (*str*, *optional*) – full path to input template file to read, over-riding the contents of the \$DESI_BASIS_TEMPLATES environment variable.
- **onlymeta** (*Bool*, *optional*) – read just the metadata table and return
- **verbose** – bool Be verbose. (Default: False)

Returns Tuple of (outflux, outwave, meta) where outflux is an Array [ntemplate,npix] of flux values [erg/s/cm²/Å]; outwave is an Array [npix] of wavelengths for FLUX [Angstrom]; meta is a Meta-data table for each object. The contents of this table varies depending on what OBJTYPE has been read.

Raises

- `EnvironmentError` – If the required \$DESI_BASIS_TEMPLATES environment variable is not set.
- `IOError` – If the basis template file is not found.

`desisim.io.read_cosmics` (*filename*, *expid=1*, *shape=None*, *jitter=True*)

Reads a dark image with cosmics from the input filename.

The input might have multiple dark images; use the *expid%n* image where *n* is the number of images in the input cosmics file.

Parameters

- **filename** – FITS filename with EXTNAME=IMAGE-, IVAR-, MASK-* HDUs
- **expid** – integer, use *expid % n* image where *n* is number of images
- **shape** – (ny, nx, optional) tuple for output image shape
- **jitter** (*bool*, *optional*) – If True (default), apply random flips and rolls so you don't get the exact same cosmics every time

Returns `desisim.image.Image` object with attributes pix, ivar, mask

`desisim.io.read_simspec` (*filename, cameras=None, comm=None, readflux=True, readphot=True*)
Read a simspect file and return a SimSpec object

Parameters `filename` – input simspect file name

Options: `cameras`: camera name or list of names, e.g. b0, r1, z9 `comm`: MPI communicator `readflux`: if True (default), include flux `readphot`: if True (default), include per-camera photons

`desisim.io.smdir` (*night=None, expid=None, mkdir=False*)
Return `$DESI_SPECTRO_SIM/$PIXPROD/{night}` If `mkdir` is True, create directory if needed

`desisim.io.write_simpix` (*outfile, image, camera, meta*)
Write simpix data to outfile.

Parameters

- **outfile** – output file name, e.g. from `io.findfile('simpix', ...)`
- **image** – 2D noiseless simulated image (`numpy.ndarray`)
- **meta** – dict-like object that should include `FLAVOR` and `EXPTIME`, e.g. from HDU0 FITS header of input simspect file

`desisim.io.write_simspec` (*sim, truth, fibermap, obs, expid, night, objmeta=None, outdir=None, filename=None, header=None, overwrite=False*)

Write a simspect file

Parameters

- **sim** (*Simulator*) – specsim Simulator object
- **truth** (*Table*) – truth metadata Table
- **fibermap** (*Table*) – fibermap Table
- **obs** (*dict-like*) – dict-like observation conditions with keys `SEEING` (arcsec), `EXPTIME` (sec), `AIRMASS`, `MOONFRAC` (0-1), `MOONALT` (deg), `MOONSEP` (deg)
- **expid** (*int*) – integer exposure ID
- **night** (*str*) – YEARMDD string
- **objmeta** (*dict*) – objtype-specific metadata
- **outdir** (*str, optional*) – output directory
- **filename** (*str, optional*) – if None, auto-derive from envvars, `night`, `expid`, and `outdir`
- **header** (*dict-like*) – header to include in HDU0
- **overwrite** (*bool, optional*) – overwrite pre-existing files

Notes

Calibration exposures can use `truth=None` and `obs=None`.

`desisim.io.write_simspec_arc` (*filename, wave, phot, header, fibermap, overwrite=False*)
Alternate writer for arc simspect files which just have photons

class `desisim.lya_mock_p1d.MockMaker` (*N2=15, dv_kms=10.0, seed=666, white_noise=False*)
Class to generate 1D mock Lyman alpha skewers.

get_density (*var_delta*, *z*, *delta*)

Transform Gaussian field delta to lognormal density, at each *z*.

get_gaussian_fields (*Ns=1*, *new_seed=None*)

Generate *Ns* Gaussian fields at redshift *z_c*.

If *new_seed* is set, it will reset random generator with it.

get_lya_skewers (*Ns=10*, *new_seed=None*)

Return *Ns* Lyman alpha skewers (wavelength, flux).

If *new_seed* is set, it will reset random generator with it.

get_redshifts ()

Get redshifts for each cell in the array (centered at *z_c*).

`desisim.lya_mock_pld.get_tau` (*z*, *density*)

transform lognormal density to optical depth, at each *z*

`desisim.lya_mock_pld.power_amplitude` (*z*)

Add redshift evolution to the Gaussian power spectrum.

`desisim.lya_mock_pld.power_kms` (*z_c*, *k_kms*, *dv_kms*, *white_noise*)

Return Gaussian PID at different wavenumbers *k_kms* (in s/km), fixed *z_c*.

Other arguments: *dv_kms*: if non-zero, will multiply power by top-hat kernel of this width *white_noise*: if set to True, will use constant power of 100 km/s

2.3.9 desisim.lya_spectra

Function to simulate a QSO spectrum including Lyman-alpha absorption.

`desisim.lya_spectra.apply_lya_transmission` (*qso_wave*, *qso_flux*, *trans_wave*, *trans*)

Apply transmission to input flux, interpolating if needed. Note that the transmission might include Lyman-beta and metal absorption, so we should probably change the name of this function.

Parameters

- **qso_wave** – 1D[nwave] array of QSO wavelengths
- **qso_flux** – 2D[nqso, nwave] array of fluxes
- **trans_wave** – 1D[ntranswave] array of transmission wavelength samples
- **trans** – 2D[nqso, ntranswave] transmissions [0-1]

Returns `output_flux[nqso, nwave]`

This routine simply apply the transmission the only thing besides multiplication is a wavelength interpolation of transmission to the QSO wavelength grid

`desisim.lya_spectra.apply_metals_transmission` (*qso_wave*, *qso_flux*, *trans_wave*, *trans*,
metals)

Apply metal transmission to input flux, interpolating if needed. The input transmission should be only due to lya, if not has no meaning. This function should not be used in London mocks with version > 2.0, since these have their own metal transmission already in the files, and even the “TRANSMISSION” HDU includes already Lyman beta.

Parameters

- **qso_wave** – 1D[nwave] array of QSO wavelengths
- **qso_flux** – 2D[nqso, nwave] array of fluxes

- **trans_wave** – 1D[ntranswave] array of lya transmission wavelength samples
- **trans** – 2D[nqso, ntranswave] transmissions [0-1]
- **metals** – list of metal names to use

Returns output_flux[nqso, nwave]

`desisim.lya_spectra.get_spectra` (*lyafile*, *nqso=None*, *wave=None*, *templateid=None*,
normfilter='sdss2010-g', *seed=None*, *rand=None*, *qso=None*,
add_dlas=False, *debug=False*, *nocolorcuts=True*)

Generate a QSO spectrum which includes Lyman-alpha absorption.

Parameters

- **lyafile** (*str*) – name of the Lyman-alpha spectrum file to read.
- **nqso** (*int*, *optional*) – number of spectra to generate (starting from the first spectrum; if more flexibility is needed use TEMPLATEID).
- **wave** (*numpy.ndarray*, *optional*) – desired output wavelength vector.
- **templateid** (*int numpy.ndarray*, *optional*) – indices of the spectra (0-indexed) to read from LYAFILE (default is to read everything). If provided together with NQSO, TEMPLATEID wins.
- **normfilter** (*str*, *optional*) – normalization filter
- **seed** (*int*, *optional*) – Seed for random number generator.
- **rand** (*numpy.RandomState*, *optional*) – RandomState object used for the random number generation. If provided together with SEED, this optional input supersedes the numpy.RandomState object instantiated by SEED.
- **qso** (*desisim.templates.QSO*, *optional*) – object with which to generate individual spectra/templates.
- **add_dlas** (*bool*) – Inject damped Lya systems into the Lya forest These are done according to the current best estimates for the incidence dN/dz (Prochaska et al. 2008, ApJ, 675, 1002) Set in calc_lz These are *not* inserted according to overdensity along the sightline
- **nocolorcuts** (*bool*, *optional*) – Do not apply the fiducial rZW1W2 color-cuts cuts (default True).

Returns (flux, wave, meta, dla_meta) where:

- flux (*numpy.ndarray*): Array [nmodel, npix] of observed-frame spectra (erg/s/cm²/Å).
- wave (*numpy.ndarray*): Observed-frame [npix] wavelength array (Angstrom).
- meta (*astropy.Table*): Table of meta-data [nmodel] for each output spectrum with columns defined in `desisim.io.empty_metatable` plus RA, DEC.
- objmeta (*astropy.Table*): Table of additional object-specific meta-data [nmodel] for each output spectrum with columns defined in `desisim.io.empty_metatable`.
- dla_meta (*astropy.Table*): Table of meta-data [ndla] for the DLAs injected into the spectra. Only returned if `add_dlas=True`

Note: *dla_meta* is only included if `add_dlas=True`.

`desisim.lya_spectra.read_lya_skewers` (*lyafile*, *indices=None*, *read_dlas=False*,
add_metals=False, *add_lyb=False*)

Reads Lyman alpha transmission skewers (from CoLoRe, format v2.x.y)

Parameters **lyafile** – full path to input FITS filename

Options: indices: indices of input file to sub-select read_dlas: try read DLA HDU from file add_metals: try to read metals HDU and multiply transmission

Returns wave[nwave] transmission[nlya, nwave] metadata[nlya] dlas[ndla] (if read_dlas=True, otherwise None)

Input file must have WAVELENGTH, TRANSMISSION, and METADATA HDUs

2.3.10 desisim.pixelsplines

Pixel-integrated spline utilities.

Written by A. Bolton, U. of Utah, 2010-2013.

exception desisim.pixelsplines.**PixSplineError** (*value*)

class desisim.pixelsplines.**PixelSpline** (*pixbound, flux*)
Pixel Spline object class.

Initialize as follows: PS = PixelSpline(pixbound, flux) where pixbound = array of pixel boundaries in baseline units and flux = array of specific flux values in baseline units.

Assumptions: ‘pixbound’ should have one more element than ‘flux’, and units of ‘flux’ are -per-unit-baseline, for the baseline units in which pixbound is expressed, averaged over the extent of each pixel.

point_evaluate (*xnew, missing=0.0*)

Evaluate underlying pixel spline at array of points BUG: input currently needs to be at least 1D array.

resample (*pb_new*)

Method to resample a pixelspline analytically onto a new set of pixel boundaries.

class desisim.pixelsplines.**WeightedRebinCoadder** (*fluxes, invvars, pixbounds*)
Objet class for weighted rebinning and coaddition of spectra

Initialize as follows: WRC = WeighedRebinCoadder(fluxes, invvars, pixbounds) where fluxes = list of arrays of specific flux values invvars = list of arrays of associated inverse variances pixbounds = list of arrays of pixel boundaries in baseline units

desisim.pixelsplines.**cen2bound** (*pixelcen*)

Convenience function to do the obvious thing to transform pixel centers to pixel boundaries.

desisim.pixelsplines.**compute_duck_slopes** (*pixbound, flux*)

Compute the slope of the illuminating quadratic spline at the locations of the ‘ducks’, i.e., the pixel boundaries, given the integrated flux per unit baseline within the pixels.

ARGUMENTS: pixbound: (npix + 1) ndarray of pixel boundaries, in units of wavelength or log-wavelength or frequency or whatever you like. flux: (npix) ndarray of spectral flux (energy or counts) per abscissa unit, averaged over the extent of the pixel

RETURNS: an (npix+1) ndarray of the slope of the underlying/illuminating flux per unit abscissa spectrum at the position of the pixel boundaries, a.k.a. ‘ducks’. The end conditions are taken to be zero slope, so the exterior points of the output are zeros.

desisim.pixelsplines.**gauss_blur_matrix** (*pixbound, sig_conv*)

Function to generate a Gaussian blurring matrix for a pixelized spectrum, from specified pixel boundaries and ‘sigma’ vector. The matrix will be flux-conserving if the spectrum to which it is applied has units of ‘counts per unit x’, and pixbound and sig_conv both have units of x.

pixbound should have one more element than sig_conv.

Output is a scipy sparse matrix that can implement the blurring as: $\text{blurflux} = \text{gauss_blur_matrix} * \text{flux}$ where 'flux' has the same dimensions as 'sig_conv'.

2.3.11 desisim.qso_template

Stuff dealing with QSO templates.

2.3.12 desisim.qso_template.desi_qso_templ

Module for Fitting PCA to the BOSS QSOs

01-Dec-2014 by JXP

```
desisim.qso_template.desi_qso_templ.chk_desi_qso_templates (infil=None,
                                                            outfil=None,
                                                            N_perz=100)

desisim.qso_template.desi_qso_templ.desi_qso_templates (z_wind=0.2,   zmnx=(0.4,
4.0),                       outfil=None,
N_perz=500,
boss_pca_fil=None,
wvmnx=(3500.0, 10000.0),
rebin_wave=None,
rstate=None,
sdss_pca_fil=None,
no_write=False,           red-
shift=None,               seed=None,
old_read=False,          ipad=40,
cosmo=None)
```

Generate QSO templates for DESI

Rebins to input wavelength array (or log10 in wvmnx)

Parameters

- **z_wind** (*float, optional*) – Window for sampling PCAs
- **zmnx** (*tuple, optional*) – Min/max for generation
- **N_perz** (*int, optional*) – Number of draws per redshift window
- **old_read** (*bool, optional*) – Read the files the old way
- **seed** (*int, optional*) – Seed for the random number state
- **rebin_wave** (*ndarray, optional*) – Input wavelengths for rebinning
- **wvmnx** (*tuple, optional*) – Wavelength limits for rebinning (not used with rebin_wave)
- **redshift** (*ndarray, optional*) – Redshifts desired for the templates
- **ipad** (*int, optional*) – Padding for enabling enough models
- **cosmo** (*astropy.cosmology.core, optional*) – Cosmology instantiation from astropy.cosmology.code

Returns

- **wave** (*ndarray*) – Wavelengths that the spectra were rebinned to
- **flux** (*ndarray (2D; flux vs. model)*)

- **z** (*ndarray*) – Redshifts

`desisim.qso_template.desi_qso_template.fig_desi_template_z_i` (*outfil=None, boss_fil=None, flg=0*)

flg = 0: Redshift flg = 1: imag

`desisim.qso_template.desi_qso_template.mean_template_zi` (*zimag, debug=False, i_wind=0.1, z_wind=0.05, boss_pca_fil=None*)

Generate ‘mean’ templates at given z,i

Parameters

- **zimag** (*list of tuples*) – Redshift, imag pairs for the templates
- **i_wind** (*float (0.1 mag)*) – Window for smoothing imag
- **z_wind** (*float (0.05 mag)*) – Window for smoothing redshift

`desisim.qso_template.desi_qso_template.repackage_coeff` (*boss_pca_fil=None, sdss_pca_fil=None, outfil='qso_templates_v2.0.fits'*)

Repackage the coefficients and redshifts into a single FITS file

Returns

`desisim.qso_template.desi_qso_template.tst_random_set` ()

Generate a small set of random templates for testing :return:

2.3.13 desisim.qso_template.fit_boss_qsos

Module for Fitting PCA to the BOSS QSOs

01-Dec-2014 by JXP

`desisim.qso_template.fit_boss_qsos.do_boss_lya_parallel` (*istart, iend, cut_Lya, output, debug=False*)

Generate PCA coeff for the BOSS Ly α DR10 dataset, v2.1

Parameters **cut_Lya** (*boolean (True)*) – Avoid using the Ly α forest in the analysis

`desisim.qso_template.fit_boss_qsos.do_sdss_lya_parallel` (*istart, iend, cut_Lya, output, debug=False*)

Generate PCA coeff for the SDSS DR7 dataset, 0.5<z<2

Parameters **cut_Lya** (*boolean (True)*) – Avoid using the Ly α forest in the analysis

`desisim.qso_template.fit_boss_qsos.failed_parallel` ()

Collision with np.dot Might fix with OPENBLAS_NUM_THREADS=1

`desisim.qso_template.fit_boss_qsos.fit_eigen` (*flux, ivar, eigen_flux*)

Fit the spectrum with the eigenvectors. Pass back the coefficients

`desisim.qso_template.fit_boss_qsos.read_qso_eigen` (*eigen_fil=None*)

Input the QSO Eigenspectra

`desisim.qso_template.fit_boss_qsos.splice_fits` (*flg=0*)

Splices together the various PCA fits for SDSS or BOSS

flg: int (0) 0=BOSS, 1=SDSS

2.3.14 desisim.qso_template.qso_pca

Module for generate QSO PCA templates

24-Nov-2014 by JXP

```
desisim.qso_template.qso_pca.do_boss_lya_parallel(istart, iend, output, debug=False,  
                                                cut_Lya=True)
```

Generate PCA coeff for the BOSS Lya DR10 dataset, v2.1

Parameters `cut_Lya` (*boolean (True)*) – Avoid using the Lya forest in the analysis

```
desisim.qso_template.qso_pca.fit_eigen(flux, ivar, eigen_flux)
```

Fit the spectrum with the eigenvectors. Pass back the coefficients

```
desisim.qso_template.qso_pca.read_qso_eigen(eigen_fil=None)
```

Input the QSO Eigenspectra

2.3.15 desisim.qso_template.tests

Module for generate QSO PCA templates

24-Nov-2014 by JXP

I don't think the documentation of this module is correct.

2.3.16 desisim.quickcat

Code for quickly generating an output zcatalog given fiber assignment tiles, a truth catalog, and optionally a previous zcatalog.

```
desisim.quickcat.get_median_obsconditions(tileids)
```

Gets the observational conditions for a set of tiles.

Parameters `tileids` – list of tileids that were observed

Returns

Table with the observational conditions for every tile.

It includes at least the following columns:

```
'TILEID': array of tile IDs  
'AIRMASS': array of airmass values on a tile  
'EBMV': array of E(B-V) values on a tile  
'LINTRANS': array of atmospheric transparency during spectro obs;   
↳ floats [0-1]  
'MOONFRAC': array of moonfraction values on a tile.  
'SEEING': array of FWHM seeing during spectroscopic observation on a   
↳ tile.
```

```
desisim.quickcat.get_observed_redshifts(targets, truth, targets_in_tile, obscon-  
                                         ditions, parameter_filename=None, ig-  
                                         nore_obscondition=False)
```

Returns observed z, zerr, zwarn arrays given true object types and redshifts

Parameters

- `targets` – target catalog table; currently used only for target mask bits
- `truth` – truth table with OIIFLUX, TRUEZ

- **targets_in_tile** – dictionary. Keys correspond to tileids, its values are the arrays of targetids observed in that tile.
- **obsconditions** – table observing conditions with columns ‘TILEID’: array of tile IDs ‘AIRMASS’: array of airmass values on a tile ‘EBMV’: array of E(B-V) values on a tile ‘LINTRANS’: array of atmospheric transparency during spectro obs; floats [0-1] ‘MOON-FRAC’: array of moonfraction values on a tile. ‘SEEING’: array of FWHM seeing during spectroscopic observation on a tile.
- **parameter_filename** – yaml file with quickcat parameters
- **ignore_obscondition** – if True, no variation of efficiency with obs. conditions (adjustment of exposure time should correct for mean change of S/N)

Returns tuple of (zout, zerr, zwarn)

`desisim.quickcat.get_redshift_efficiency` (*simtype, targets, truth, targets_in_tile, obsconditions, params, ignore_obscondition=False*)

Simple model to get the redshift efficiency from the observational conditions or observed magnitudes+redshuft

Parameters

- **simtype** – ELG, LRG, QSO, MWS, BGS
- **targets** – target catalog table; currently used only for TARGETID
- **truth** – truth table with OIIFLUX, TRUEZ
- **targets_in_tile** – dictionary. Keys correspond to tileids, its values are the arrays of targetids observed in that tile.
- **obsconditions** – table observing conditions with columns ‘TILEID’: array of tile IDs ‘AIRMASS’: array of airmass values on a tile ‘EBMV’: array of E(B-V) values on a tile ‘LINTRANS’: array of atmospheric transparency during spectro obs; floats [0-1] ‘MOON-FRAC’: array of moonfraction values on a tile. ‘SEEING’: array of FWHM seeing during spectroscopic observation on a tile.
- **parameter_filename** – yaml file with quickcat parameters
- **ignore_obscondition** – if True, no variation of efficiency with obs. conditions (adjustment of exposure time should correct for mean change of S/N)

Returns

tuple of arrays (observed, p) both with same length as targets

observed: boolean array of whether the target was observed in these tiles

p: probability to get this redshift right

`desisim.quickcat.get_zeff_obs` (*simtype, obsconditions*)

`desisim.quickcat.quickcat` (*tilefiles, targets, truth, fassignhdu='FIBERASSIGN', zcat=None, obsconditions=None, perfect=False*)

Generates quick output zcatalog

Parameters

- **tilefiles** – list of fiberassign tile files that were observed
- **targets** – astropy Table of targets
- **truth** – astropy Table of input truth with columns TARGETID, TRUEZ, and TRUETYPE
- **zcat** (*optional*) – input zcatalog Table from previous observations

- **obsconditions** (*optional*) – Table or ndarray with observing conditions from surveysim
- **perfect** (*optional*) – if True, treat spectro pipeline as perfect with input=output, otherwise add noise and zwarn!=0 flags

Returns zcatalog astropy Table based upon input truth, plus ZERR, ZWARN, NUMOBS, and TYPE columns

`desisim.quickcat.reverse_dictionary(a)`

Inverts a dictionary mapping.

Parameters *a* – input dictionary.

Returns output reversed dictionary.

Return type *b*

2.3.17 desisim.quicksurvey

Code for quickly simulating the survey results given a mock catalog and a list of tile epochs to observe.

Directly depends on the following DESI products:

- desitarget.mtl
- `desisim.quickcat`
- fiberassign

class `desisim.quicksurvey.SimSetup` (*output_path, targets_path, fiberassign, exposures, fiberassign_dates*)

Setup to simulate the DESI survey

output_path

Path to write the outputs.x

Type *str*

targets_path

Path where the files targets.fits can be found

Type *str*

epochs_path

Path where the epoch files can be found.

Type *str*

fiberassign

Name of the fiberassign script

Type *str*

template_fiberassign

Filename of the template input for fiberassign

Type *str*

n_epochs

number of epochs to be simulated.

Type *int*

backup_epoch_data (*epoch_id=0*)

Deletes files in the temporary output directory

Parameters **epoch_id** (*int*) – Epoch’s ID to backup/copy from the output directory.

cleanup_directories ()

Deletes files in the temporary output directory

create_directories ()

Creates output directories to store simulation results.

create_surveyfile (*epoch*)

Creates text file of tiles survey_list.txt to be used by fiberassign

Parameters **epoch** (*int*) – epoch of tiles to write

Notes

The file is written to the temporary directory in self.tmp_output_path

epoch_data_exists (*epoch_id=0*)

Check epoch directory for zcat.fits and mtl.fits files.

simulate ()

Simulate the DESI setup described by a SimSetup object.

simulate_epoch (*epoch, truth, targets, perfect=False, zcat=None*)

Core routine simulating a DESI epoch,

Parameters

- **epoch** (*int*) – epoch to simulate
- **perfect** (*boolean*) – Default: False. Selects whether how redshifts are taken from the truth file. True: redshifts are taken without any error from the truth file. False: redshifts include uncertainties.
- **truth** (*Table*) – Truth data
- **targets** (*Table*) – Targets data
- **zcat** (*Table*) – Redshift Catalog Data

Notes

This routine simulates three steps: * Merged target list creation * Fiber allocation * Redshift catalogue construction

update_observed_tiles (*epoch*)

Creates the list of tilefiles to be gathered to build the redshift catalog.

2.3.18 desisim.scripts

Main functions and command-line parsing. Generate S/N plots as a function of object type for the current production

Read fibermaps and zbest files to generate QA related to redshifts and compare against the ‘true’ values

2.3.19 desisim.spec_qa

Tools for DESI QA with simulations It does not cover cosmology simulations.

2.3.20 desisim.spec_qa.high_level

Module to run high_level QA on a given DESI run Written by JXP on 3 Sep 2015

```
desisim.spec_qa.high_level.get_meta()
    Get META data on production

desisim.spec_qa.high_level.main()
    Runs the process
```

2.3.21 desisim.spec_qa.redshifts

Module to run high_level QA on a given DESI run

Written by JXP on 3 Sep 2015

```
desisim.spec_qa.redshifts.calc_dz(simz_tab)
    Calcualte deltaz/(1+z) for a given simz_tab

desisim.spec_qa.redshifts.calc_dzsig(simz_tab)
    Calcualte deltaz/sig(z) for a given simz_tab

desisim.spec_qa.redshifts.calc_obj_stats(simz_tab, objtype)
    Calculate redshift statistics for a given objtype
```

Parameters

- **simz_tab** (*Table*) – TODO: document this
- **objtype** (*str*) – Object type, e.g. ‘ELG’, ‘LRG’

Returns *stat_dict* – Survey results for a given object type

Return type *dict*

```
desisim.spec_qa.redshifts.criteria(simz_tab, objtype=None, dvlimit=None)
    Analyze the input table for various criteria
```

Parameters

- **simz_tab** (*Table*) –
- **objtype** (*str, optional -- Restrict analysis to a specific object type*) –

Returns

- **objtype_mask** (*ndarray*) – Match to input objtype (if any given)
- **z_mask** (*ndarray*) – Analyzed by the redshift analysis software
- **survey_mask** (*ndarray*) – Part of the DESI survey (not filler)
- **dv_mask** (*ndarray*) – Satisfies the dv criterion; Either specific to each objtype or using an input dvlimit
- **zwarn_mask** (*ndarray*) – ZWARN=0

`desisim.spec_qa.redshifts.dz_summ` (*simz_tab*, *outfile=None*, *pdict=None*, *min_count=20*)
 Generate a summary figure comparing zfind to ztruth.

Parameters

- **simz_tab** (*Table*) – Table of redshift information.
- **pp** (*PdfPages object*) – This parameter is not documented.
- **pdict** (*dict*) – Guides the plotting parameters
- **min_count** (*int, optional*) – This parameter is not documented.

`desisim.spec_qa.redshifts.load_z` (*fibermap_files*, *zbest_files=None*, *outfil=None*)
 Load input and output redshift values for a set of exposures

Parameters

- **fibermap_files** (*list*) – List of fibermap files; None of these should be calibration..
- **zbest_files** (*list, optional*) – List of zbest output files Slurped from fibermap info if not provided
- **outfil** (*str, optional*) – Output file for the table

Returns

- **simz_tab** (*astropy.Table*) – Merged table of simpsec data
- **zb_tab** (*astropy.Table*) – Merged table of zbest output

`desisim.spec_qa.redshifts.match_truth_z` (*simz_tab*, *zb_tab*, *mini_read=False*, *outfil=None*)
 Match truth and zbest tables :param simz_tab: astropy.Table; Either generated from load_z() or read from disk via ‘truth.fits’ :param zb_tab: astropy.Table; Either generated from load_z() or read from disk via ‘zcatalog-mini.fits’ :param mini_read: bool, optional; Tables were read from the summary tables written to disk :param outfil: str, optional :return: simz_tab: modified in place

`desisim.spec_qa.redshifts.obj_fig` (*simz_tab*, *objtype*, *summ_stats*, *outfile=None*)
 Generate QA plot for a given object type

`desisim.spec_qa.redshifts.obj_requirements` (*zstats*, *objtype*)
 Assess where a given objtype passes the requirements Requirements from Doc 318 (August 2014)

Parameters

- **zstats** (*Object*) – This parameter is not documented.
- **objtype** (*str*) – Object type, e.g. ‘ELG’, ‘LRG’

Returns Pass/fail dict

Return type dict

`desisim.spec_qa.redshifts.plot_slices` (*x*, *y*, *ok*, *bad*, *x_lo*, *x_hi*, *y_cut*, *num_slices=5*,
min_count=100, *axis=None*)

Scatter plot with 68, 95 percentiles superimposed in slices.

Requires that the matplotlib package is installed.

Parameters

- **x** (*array of float*) – X-coordinates to scatter plot. Points outside [*x_lo*, *x_hi*] are not displayed.
- **y** (*array of float*) – Y-coordinates to scatter plot. Y values are assumed to be roughly symmetric about zero.
- **ok** (*array of bool*) – Array of booleans that identify which fits are considered good.

- **bad** (*array of bool*) – Array of booleans that identify which fits have failed catastrophically.
- **x_lo** (*float*) – Minimum value of x to plot.
- **x_hi** (*float*) – Maximum value of x to plot.
- **y_cut** (*float*) – The target maximum value of $|y|$. A dashed line at this value is added to the plot, and the vertical axis is clipped at $|y| = 1.25 \times y_{cut}$ (but values outside this range are included in the percentile statistics).
- **num_slices** (*int*) – Number of equally spaced slices to divide the interval $[x_{lo}, x_{hi}]$ into.
- **min_count** (*int*) – Do not use slices with fewer points for superimposed percentile statistics.
- **axis** (*matplotlib axis object or None*) – Uses the current axis if this is None.

`desisim.spec_qa.redshifts.slice_simz` (*simz_tab, objtype=None, z_analy=False, survey=False, catastrophic=False, goodz=False, all_zwarn0=False, **kwargs*)

Slice input `simz_tab` in one of many ways

Parameters

- **z_analy** (*bool, optional*) – redshift analysis required?
- **all_zwarn0** (*bool, optional*) – Ignores catastrophic failures in the slicing to return all sources with `ZWARN==0`
- **survey** (*bool, optional*) – Only include objects that satisfy the Survey requirements e.g. ELGs with sufficient `OII_flux`
- **catastrophic** (*bool, optional*) – Restrict to catastrophic failures
- **goodz** (*bool, optional*) – Restrict to good redshifts
- **all_zwarn0** – Restrict to `ZWARN=0` cases
- ****kwargs** (*passed to criteria*) –

Returns `simz_table`

Return type Table cut by input parameters

`desisim.spec_qa.redshifts.spectype_confusion` (*simz_tab, zb_tab=None*)

Generate a Confusion Matrix for spectral types See the `Confusion_matrix_spectypes` Notebook in `docs/nb` for an example

Parameters

- **simz_tab** (*Table*) – Truth table; may be input from `truth.fits`
- **zb_tab** (*Table optional*) – `zcatalog/zbest` table; may be input from `zcatalog-mini.fits` If provided, used to match the `simz_tab` to the `zbest` quantities

Returns

- **simz_tab** (*astropy.Table*) – Merged table of `simpsec` data
- **results** (*dict*) – Nested dict. First key is the `TRUESPECTYPE` Second key is the `SPECTYPE` e.g. `results['QSO']['QSO']` reports the number of True QSO classified as QSO `results['QSO']['Galaxy']` reports the number of True QSO classified as Galaxy

`desisim.spec_qa.redshifts.summ_fig` (*simz_tab, summ_tab, meta, outfile=None*)

Generate summary `summ_fig` :param `simz_tab`: :param `summ_tab`: :param `meta`: :param `outfile`: :return:

`desisim.spec_qa.redshifts.summ_stats(simz_tab)`

Generate summary stats

Parameters `simz_tab` (*Table*) – Table summarizing redshifts

Returns List of summary stat dicts

Return type `lis`

`desisim.spec_qa.redshifts.zstats(simz_tab, objtype=None, dvlimit=None, count=False, survey=False)`

Perform statistics on the input truth+z table
 good = Satisfies dv criteria and ZWARN==0
 fail = Fails dv criteria with ZWARN==0 (catastrophic failures)
 miss = Satisfies dv criteria but ZWARN!=0 (missed opportunities)
 lost = Fails dv criteria and ZWARN!=0 (lost, but at least we knew it)

Parameters

- `simz_tab` –
- `objtype` –
- `dvlimit` – float, optional – Over-rides object specific dv limits
- `count` – bool, optional
- `survey` – bool, optional – Restrict to targets meeting the Survey criteria (e.g. ELG flux)

Returns just the raw counts of each category :: `ngood`, `nfail`, `nmiss`, `nlost` else: percentile of each relative to `ntot`, and `ntot`

Return type if `count=True`

2.3.22 desisim.spec_qa.s2n

Module to examine S/N in object spectra

`desisim.spec_qa.s2n.load_all_s2n_values(nights, channel, sub_exposures=None)`

Calculate S/N values for a set of spectra from an input list of nights

Parameters

- `nights` – list
- `channel` – str ('b','r','z')
- `sub_exposures` –

Returns

`dict` Contains all the S/N info for all nights in the given channel

Return type `fdict`

`desisim.spec_qa.s2n.load_s2n_values(objtype, nights, channel, sub_exposures=None)`

DEPRECATED

Calculate S/N values for a set of spectra

Parameters

- `objtype` – str
- `nights` – list
- `channel` – str
- `sub_exposures` –

Returns

dict Contains S/N info

Return type fdict

`desisim.spec_qa.s2n.obj_s2n_wave` (*s2n_dict, wv_bins, flux_bins, otype, outfile=None, ax=None*)
Generate QA of S/N for a given object type

`desisim.spec_qa.s2n.obj_s2n_z` (*s2n_dict, z_bins, flux_bins, otype, outfile=None, ax=None*)
Generate QA of S/N for a given object type vs. z (mainly for ELG)

`desisim.spec_qa.s2n.parse_s2n_values` (*objtype, fdict*)
Parse the input set of S/N measurements on objtype

Parameters

- **objtype** – str
- **fdict** – dict Contains all the S/N info for all nights in a given channel

Returns

dict Contains all the S/N info for the given objtype

Return type pdict

2.3.23 `desisim.spec_qa.redshifts`

Module to run high_level QA on a given DESI run

Written by JXP on 3 Sep 2015

`desisim.spec_qa.utils.catastrophic_dv` (*objtype*)
Pass back catastrophic velocity limit for given objtype From DESI document 318 (August 2014) in docdb

Parameters **objtype** (*str*) – Object type, e.g. ‘ELG’, ‘LRG’

`desisim.spec_qa.utils.elg_flux_lim` (*z, oii_flux*)
Assess which objects pass the ELG flux limit Uses DESI document 318 from August 2014

Parameters

- **z** (*ndarray*) – ELG redshifts
- **oii_flux** (*ndarray*) – [OII] fluxes

`desisim.spec_qa.utils.get_sty_otype` ()
Styles for plots

`desisim.spec_qa.utils.match_otype` (*tbl, objtype*)
Generate a mask for the input objtype :param tbl: :param objtype: str :return: targets: bool mask

2.3.24 `desisim.specsim`

DESI wrapper functions for external specsim classes.

`desisim.specsim.get_simulator` (*config='desi', num_fibers=1, camera_output=True*)
returns new or cached specsim.simulator.Simulator object

Also adds placeholder for BGS fiberloss if that isn't already in the config

2.3.25 desisim.targets

Utility functions for working with simulated targets.

`desisim.targets._default_wave` (*wavemin=None, wavemax=None, dw=0.2*)
Construct and return the default wavelength vector.

`desisim.targets.get_simtype` (*spectype, desi_target, bgs_target, mws_target*)
Derive the simulation type from the redshift spectype and target bits

Parameters

- **spectype** – array of ‘GALAXY’, ‘QSO’, ‘STAR’
- ***_target** – target mask bits

Returns array of simulation types: ELG, LRG, QSO, BGS, ...

TODO: add subtypes of STAR

`desisim.targets.get_targets` (*nspec, program, tileid=None, seed=None, specify_targets={}, specmin=0*)

Generates a set of targets for the requested program

Parameters

- **nspec** – (int) number of targets to generate
- **program** – (str) program name DARK, BRIGHT, GRAY, MWS, BGS, LRG, ELG, ...

Options:

- **tileid**: (int) tileid, used for setting RA,dec
- **seed**: (int) random number seed
- **specify_targets**: (dict of dicts) **Define target properties like magnitude and redshift** for each target class. Each objtype has its own key,value pair see `simspec.templates.specify_galparams_dict()` or `simsepc.templates.specify_starparams_dict()`
- **specmin**: (int) first spectrum number (0-indexed)

Returns

- fibermap
- targets as tuple of (flux, wave, meta)

`desisim.targets.get_targets_parallel` (*nspec, program, tileid=None, nproc=None, seed=None, specify_targets={}*)

Parallel wrapper for `get_targets()`

`nproc` (int) is number of multiprocessing processes to use.

`desisim.targets.sample_nz` (*objtype, n*)

Given *objtype* = ‘LRG’, ‘ELG’, ‘QSO’, ‘STAR’, ‘STD’ return array of *n* redshifts that properly sample *n(z)* from `$DESIMODEL/data/targets/nz*.dat`

`desisim.targets.sample_objtype` (*nobj, program*)

Return a random sampling of object types (dark, bright, MWS, BGS, ELG, LRG, QSO, STD, BAD_QSO)

Parameters `nobj` – number of objects to generate

Returns

(**true_objtype**, **target_objtype**) where **true_objtype** is the array of what type the objects actually are and **target_objtype** is the array of type they were targeted as

Notes

- Actual fiber assignment will result in higher relative fractions of LRGs and QSOs in early passes and more ELGs in later passes.
- Also ensures at least 2 sky and 1 stdstar, even if nobj is small

2.3.26 desisim.templates

Functions to simulate spectral templates for DESI.

```
class desisim.templates.BGS (minwave=3600.0, maxwave=10000.0, cdelt=0.2, wave=None,
                             transient=None, tr_fluxratio=(0.01, 1.0), tr_epoch=(-10, 10),
                             include_mgii=False, colorcuts_function=None,
                             normfilter_north='BASS-r', normfilter_south='decam2014-r',
                             baseflux=None, basewave=None, basemeta=None)
```

Generate Monte Carlo spectra of bright galaxy survey galaxies (BGSs).

```
make_templates (nmodel=100, zrange=(0.01, 0.4), magrange=(15.0, 20.0), oiihbrange=(-1.3, 0.6),
                 logvdisp_meansig=(2.0, 0.17), minhbетаflux=0.0, trans_filter='decam2014-r',
                 redshift=None, mag=None, vdisp=None, seed=None, input_meta=None, nocolorcuts=False,
                 nocontinuum=False, agnlike=False, novdisp=False, south=True, restframe=False,
                 verbose=False)
```

Build Monte Carlo BGS spectra/templates.

See the GALAXY.make_galaxy_templates function for documentation on the arguments and inherited attributes. Here we only document the arguments that are specific to the BGS class.

Parameters

- **oiihbrange** (*float, optional*) – Minimum and maximum logarithmic [OIII] 5007/H-beta line-ratio. Defaults to a uniform distribution between (-1.3, 0.6).
- **logvdisp_meansig** (*float, optional*) – Logarithmic mean and sigma values for the (Gaussian) stellar velocity dispersion distribution. Defaults to log10-sigma=(2.0+/-0.17) km/s
- **minhbетаflux** (*float, optional*) – Minimum H-beta flux (default 0.0 erg/s/cm2).

Returns (outflux, wave, meta, objmeta) tuple where:

- outflux (numpy.ndarray): Array [nmodel, npix] of observed-frame spectra (1e-17 erg/s/cm2/Å).
- wave (numpy.ndarray): Observed-frame [npix] wavelength array (Angstrom).
- meta (astropy.Table): Table of meta-data [nmodel] for each output spectrum.
- objmeta (astropy.Table): Additional objtype-specific table data [nmodel] for each spectrum.

Raises:

class `desisim.templates.ELG` (*minwave=3600.0, maxwave=10000.0, cdelt=0.2, wave=None, transient=None, tr_fluxratio=(0.01, 1.0), tr_epoch=(-10, 10), include_mgii=False, colorcuts_function=None, normfilter_north='BASS-g', normfilter_south='decam2014-g', baseflux=None, basewave=None, basemeta=None*)

Generate Monte Carlo spectra of emission-line galaxies (ELGs).

make_templates (*nmodel=100, zrange=(0.6, 1.6), magrange=(20.0, 23.5), oiiihbrange=(-0.5, 0.2), logvdisp_meansig=(1.9, 0.15), minoiiflux=0.0, trans_filter='decam2014-r', redshift=None, mag=None, vdisp=None, seed=None, input_meta=None, nocolorcuts=False, nocontinuum=False, agnlike=False, novdisp=False, south=True, restframe=False, verbose=False*)

Build Monte Carlo ELG spectra/templates.

See the `GALAXY.make_galaxy_templates` function for documentation on the arguments and inherited attributes. Here we only document the arguments that are specific to the `ELG` class.

Parameters

- **oiiihbrange** (*float, optional*) – Minimum and maximum logarithmic [OIII] 5007/H-beta line-ratio. Defaults to a uniform distribution between (-0.5, 0.2).
- **logvdisp_meansig** (*float, optional*) – Logarithmic mean and sigma values for the (Gaussian) stellar velocity dispersion distribution. Defaults to $\log_{10}\text{-sigma}=(1.9\pm 0.15)$ km/s
- **minoiiflux** (*float, optional*) – Minimum [OII] 3727 flux (default 0.0 erg/s/cm²).

Returns (outflux, wave, meta, objmeta) tuple where:

- **outflux** (`numpy.ndarray`): Array [`nmodel`, `npix`] of observed-frame spectra (1e-17 erg/s/cm²/Å).
- **wave** (`numpy.ndarray`): Observed-frame [`npix`] wavelength array (Angstrom).
- **meta** (`astropy.Table`): Table of meta-data [`nmodel`] for each output spectrum.
- **objmeta** (`astropy.Table`): Additional objtype-specific table data [`nmodel`] for each spectrum.

Raises:

class `desisim.templates.EMSpectrum` (*minwave=3650.0, maxwave=7075.0, cdelt_kms=20.0, log10wave=None, include_mgii=False*)

Construct a complete nebular emission-line spectrum.

Read the requisite external data files and initialize the output wavelength array.

The desired output wavelength array can either be passed directly using `LOG10WAVE` (note: must be a log-base10, i.e., constant-velocity pixel array!) or via the `MINWAVE`, `MAXWAVE`, and `CDELTA_KMS` arguments.

In addition, three data files are required: `$(DESIIM)/data/recombination_lines.esv`, `$(DESIIM)/data/forbidden_lines.esv`, and `$(DESIIM)/data/forbidden_mog.fits`.

TODO (@moustakas): Incorporate AGN-like emission-line ratios. TODO (@moustakas): Think about how to best include dust attenuation in the lines.

Parameters

- **minwave** (*float, optional*) – Minimum value of the output wavelength array [Angstrom, default 3600].
- **maxwave** (*float, optional*) – Minimum value of the output wavelength array [Angstrom, default 10000].

- **cdelt_kms** (*float, optional*) – Spacing of the output wavelength array [km/s, default 20].
- **log10wave** (*numpy.ndarray, optional*) – Input/output wavelength array (log10-Angstrom, default None).
- **include_mgii** (*bool, optional*) – Include Mg II in emission (default False).

log10wave

Wavelength array constructed from the input arguments.

Type `numpy.ndarray`

line

Table containing the laboratory (vacuum) wavelengths and nominal line-ratios for several dozen forbidden and recombination nebular emission lines.

Type `astropy.Table`

forbidmog

Table containing the mixture of Gaussian parameters encoding the forbidden emission-line priors.

Type `GaussianMixtureModel`

oiidoublet

Intrinsic [OIII] 5007/4959 doublet ratio (set by atomic physics).

Type `float32`

niidoublet

Intrinsic [NII] 6584/6548 doublet ratio (set by atomic physics).

Type `float32`

Raises `IOError` – If the required data files are not found.

spectrum (*oiihbeta=None, oiibeta=None, niibeta=None, siihbeta=None, oiidoublet=0.73, siidoublet=1.3, linesigma=75.0, zshift=0.0, oiflux=None, hbetaflux=None, seed=None*)

Build the actual emission-line spectrum.

Building the emission-line spectrum involves three main steps. First, the `oiihbeta`, `oiibeta`, and `niibeta` emission-line ratios are either drawn from the empirical mixture of Gaussians (recommended!) or input values are used to construct the line-ratios of the strongest optical forbidden lines relative to H-beta.

Note that all three of `oiihbeta`, `oiibeta`, and `niibeta` must be specified simultaneously in order for them to be used.

Second, the requested [OII] 3726,29 and [SII] 6716,31 doublet ratios are imposed.

And finally the full emission-line spectrum is self-consistently normalized to *either* an integrated [OII] 3726,29 line-flux *or* an integrated H-beta line-flux. Generally an ELG and LRG spectrum will be normalized using [OII] while the a BGS spectrum will be normalized using H-beta. Note that the H-beta normalization trumps the [OII] normalization (in the case that both are given).

TODO (@moustakas): Add a suitably scaled nebular continuum spectrum. TODO (@moustakas): Add more emission lines (e.g., [NeIII] 3869).

Parameters

- **oiihbeta** (*float, optional*) – Desired logarithmic [OIII] 5007/H-beta line-ratio (default -0.2). A sensible range is [-0.5,0.2].
- **oiibeta** (*float, optional*) – Desired logarithmic [OII] 3726,29/H-beta line-ratio (default 0.1). A sensible range is [0.0,0.4].

- **niihbeta** (*float, optional*) – Desired logarithmic [NII] 6584/H-beta line-ratio (default -0.2). A sensible range is [-0.6,0.0].
- **siihbeta** (*float, optional*) – Desired logarithmic [SII] 6716/H-beta line-ratio (default -0.3). A sensible range is [-0.5,0.2].
- **oiidoublet** (*float, optional*) – Desired [OII] 3726/3729 doublet ratio (default 0.73).
- **siidoublet** (*float, optional*) – Desired [SII] 6716/6731 doublet ratio (default 1.3).
- **linesigma** (*float, optional*) – Intrinsic emission-line velocity width/sigma (default 75 km/s). A sensible range is [30-150].
- **zshift** (*float, optional*) – Perturb the emission lines from their laboratory (rest) wavelengths by a factor 1+ZSHIFT (default 0.0). Use with caution!
- **oiiflux** (*float, optional*) – Normalize the emission-line spectrum to this integrated [OII] emission-line flux (default None).
- **hbetaflux** (*float, optional*) – Normalize the emission-line spectrum to this integrated H-beta emission-line flux (default None).
- **seed** (*int, optional*) – input seed for the random numbers.

Returns Tuple of (emspec, wave, line), where emspec is an Array [npix] of flux values [erg/s/cm²/Å]; wave is an Array [npix] of vacuum wavelengths corresponding to FLUX [Angstrom, linear spacing]; line is a Table of emission-line parameters used to generate the emission-line spectrum.

```
class desisim.templates.GALAXY (objtype='ELG', minwave=3600.0, maxwave=10000.0,
cdelt=0.2, wave=None, transient=None, tr_fluxratio=(0.01,
1.0), tr_epoch=(-10, 10), include_mgii=False, col-
orcuts_function=None, normfilter_north='BASS-r',
normfilter_south='decam2014-r', normline='OII',
fracvdisp=(0.1, 40), baseflux=None, basewave=None,
basemeta=None)
```

Base class for generating Monte Carlo spectra of the various flavors of galaxies (ELG, BGS, and LRG).

```
_blurmatrix (vdisp, log=None)
```

Pre-compute the blur_matrix as a dictionary keyed by each unique value of vdisp.

```
lineratios (nobj, oiihbrange=(-0.5, 0.2), oiidoublet_meansig=(0.73, 0.05), agnlike=False,
rand=None)
```

Get the correct number and distribution of the forbidden and [OII] 3726/3729 doublet emission-line ratios. Note that the agnlike option is not yet supported.

Supporting oiihbrange needs a different (fast) approach. Suppressing the code below for now until it's needed.

```
make_galaxy_templates (nmodel=100, zrange=(0.6, 1.6), magrange=(20.0, 22.0),
oiihbrange=(-0.5, 0.2), logvdisp_meansig=(1.9, 0.15), minline-
flux=0.0, trans_filter='decam2014-r', seed=None, redshift=None,
mag=None, vdisp=None, input_meta=None, nocolorcuts=False,
nocontinuum=False, agnlike=False, novdisp=False, south=True,
restframe=False, verbose=False)
```

Build Monte Carlo galaxy spectra/templates.

This function chooses random subsets of the basis continuum spectra (for the given galaxy spectral type), constructs an emission-line spectrum (if desired), redshifts, convolves by the intrinsic velocity dispersion, and then finally normalizes each spectrum to a (generated or input) apparent magnitude.

In detail, each (output) model gets randomly assigned a continuum (basis) template; however, if that template doesn't pass the (spectral) class-specific color cuts (at the specified redshift), then we iterate through the rest of the templates until we find one that *does* pass the color-cuts.

The user also (optionally) has a lot of flexibility over the inputs/outputs and can specify any combination of the redshift, velocity dispersion, and apparent magnitude (in the normalization filter specified in the `GALAXY.__init__` method) inputs. Alternatively, the user can pass a complete metadata table, in order to easily regenerate spectra on-the-fly (see the documentation for the `input_meta` argument, below).

Note: The default inputs are generally set to values which are appropriate for ELGs, so be sure to alter them when generating templates for other spectral classes.

Parameters

- **nmodel** (*int*, *optional*) – Number of models to generate (default 100).
- **zrange** (*float*, *optional*) – Minimum and maximum redshift range. Defaults to a uniform distribution between (0.6, 1.6).
- **magrange** (*float*, *optional*) – Minimum and maximum magnitude in the bandpass specified by `self.normfilter_south` (if `south=True`) or `self.normfilter_north` (if `south=False`). Defaults to a uniform distribution between (20.0, 22.0).
- **oiiihbrange** (*float*, *optional*) – Minimum and maximum logarithmic [OIII] 5007/H-beta line-ratio. Defaults to a uniform distribution between (-0.5, 0.2).
- **logvdisp_meansig** (*float*, *optional*) – Logarithmic mean and sigma values for the (Gaussian) stellar velocity dispersion distribution. Defaults to $\log_{10}\text{-sigma}=1.9\pm 0.15$ km/s.
- **minlineflux** (*float*, *optional*) – Minimum emission-line flux in the line specified by `self.normline` (default 0 erg/s/cm²).
- **trans_filter** (*str*) – filter corresponding to `TRANS_FLUXRATORANGE` (default 'decam2014-r').
- **seed** (*int*, *optional*) – Input seed for the random numbers.
- **redshift** (*float*, *optional*) – Input/output template redshifts. Array size must equal `nmodel`. Ignores `zrange` input.
- **mag** (*float*, *optional*) – Input/output template magnitudes in the bandpass specified by `self.normfilter_south` (if `south=True`) or `self.normfilter_north` (if `south=False`). Array size must equal `nmodel`. Ignores `magrange` input.
- **vdisp** (*float*, *optional*) – Input/output velocity dispersions in km/s. Array size must equal `nmodel`.
- **input_meta** (*astropy.Table*) – *Input* metadata table with the following required columns: `TEMPLATEID`, `SEED`, `REDSHIFT`, `MAG`, and `MAGFILTER` (see `desisim.io.empty_metatable` for the expected data types). In addition, in order to faithfully reproduce a previous set of spectra, then `VDISP` must also be passed (normally returned in the `OBJMETA` table). If present, then all other optional inputs (`nmodel`, `redshift`, `mag`, `zrange`, `logvdisp_meansig`, etc.) are ignored.
- **nocolorcuts** (*bool*, *optional*) – Do not apply the color-cuts specified by the `self.colorcuts_function` function (default `False`).

- **nocontinuum** (*bool, optional*) – Do not include the stellar continuum in the output spectrum (useful for testing; default False). Note that this option automatically sets `nocolorcuts` to True and `transient` to False.
- **novdisp** (*bool, optional*) – Do not velocity-blur the spectrum (default False).
- **agnlike** (*bool, optional*) – Adopt AGN-like emission-line ratios (e.g., for the LRGs and some BGS galaxies) (default False, meaning we adopt star-formation-like line-ratios). Option not yet supported.
- **south** (*bool, optional*) – Apply “south” color-cuts using the DECaLS filter system, otherwise apply the “north” (MzLS+BASS) color-cuts. Defaults to True.
- **restframe** (*bool, optional*) – If True, return full resolution restframe templates instead of resampled observer frame.
- **verbose** (*bool, optional*) – Be verbose!

Returns (outflux, wave, meta, objmeta) tuple where:

- outflux (numpy.ndarray): Array [nmodel, npix] of observed-frame spectra (1e-17 erg/s/cm²/Å).
- wave (numpy.ndarray): Observed-frame [npix] wavelength array (Angstrom).
- meta (astropy.Table): Table of meta-data [nmodel] for each output spectrum.
- objmeta (astropy.Table): Additional objtype-specific table data [nmodel] for each spectrum.

Raises `ValueError`

```
class desisim.templates.LRG (minwave=3600.0, maxwave=10000.0, cdelt=0.2, wave=None,
transient=None, tr_fluxratio=(0.01, 1.0), tr_epoch=(-10,
10), colorcuts_function=None, normfilter_north='MzLS-z',
normfilter_south='decam2014-z', baseflux=None, basewave=None,
basemeta=None)
```

Generate Monte Carlo spectra of luminous red galaxies (LRGs).

```
make_templates (nmodel=100, zrange=(0.5, 1.0), magrange=(19.0, 21.5), logvdisp_meansig=(2.3,
0.1), trans_filter='decam2014-r', redshift=None, mag=None, vdisp=None,
seed=None, input_meta=None, nocolorcuts=False, novdisp=False, agnlike=False,
south=True, restframe=False, verbose=False)
```

Build Monte Carlo BGS spectra/templates.

See the `GALAXY.make_galaxy_templates` function for documentation on the arguments and inherited attributes. Here we only document the arguments that are specific to the LRG class.

Parameters

- **logvdisp_meansig** (*float, optional*) – Logarithmic mean and sigma values for the (Gaussian) stellar velocity dispersion distribution. Defaults to `log10-sigma=(2.3+/-0.1)` km/s
- **agnlike** (*bool, optional*) – adopt AGN-like emission-line ratios (not yet supported; defaults False).

Returns (outflux, wave, meta, objmeta) tuple where:

- outflux (numpy.ndarray): Array [nmodel, npix] of observed-frame spectra (1e-17 erg/s/cm²/Å).
- wave (numpy.ndarray): Observed-frame [npix] wavelength array (Angstrom).
- meta (astropy.Table): Table of meta-data [nmodel] for each output spectrum.

- `objmeta` (`astropy.Table`): Additional objtype-specific table data [`nmodel`] for each spectrum.

Raises:

```
class desisim.templates.MWS_STAR (minwave=3600.0, maxwave=10000.0, cdelt=0.2,  
wave=None, colorcuts_function=None,  
normfilter_north='BASS-r', normfilter_south='decam2014-  
r', baseflux=None, basewave=None, basemeta=None)
```

Generate Monte Carlo spectra of Milky Way Survey (magnitude-limited) stars.

```
make_templates (nmodel=100, vrad_meansig=(0.0, 200.0), magrange=(16.0, 20.0), seed=None,  
redshift=None, mag=None, input_meta=None, star_properties=None, nocolor-  
cuts=False, south=True, restframe=False, verbose=False)
```

Build Monte Carlo spectra/templates for MWS_STAR stars.

See the `SUPERSTAR.make_star_templates` function for documentation on the arguments and inherited attributes. Here we only document the arguments which are specific to the `MWS_STAR` class.

Args:

Returns (outflux, wave, meta, objmeta) tuple where:

- `outflux` (`numpy.ndarray`): Array [`nmodel`, `npix`] of observed-frame spectra (1e-17 erg/s/cm²/Å).
- `wave` (`numpy.ndarray`): Observed-frame [`npix`] wavelength array (Angstrom).
- `meta` (`astropy.Table`): Table of meta-data [`nmodel`] for each output spectrum.
- `objmeta` (`astropy.Table`): Additional objtype-specific table data [`nmodel`] for each spectrum.

Raises:

```
class desisim.templates.QSO (minwave=3600.0, maxwave=10000.0, cdelt=0.2, wave=None,  
basewave_min=1200, basewave_max=25000.0, basewave_R=8000,  
normfilter_north='BASS-r', normfilter_south='decam2014-r',  
colorcuts_function=None, balqso=False, z_wind=0.2)
```

Generate Monte Carlo spectra of quasars (QSOs).

```
_sample_pcacoeff (nsample, coeff, samplerand)
```

Draw from the distribution of PCA coefficients.

```
make_templates (nmodel=100, zrange=(0.5, 4.0), magrange=(17.5, 22.7), seed=None, red-  
shift=None, mag=None, input_meta=None, N_perz=40, maxiter=20, uni-  
form=False, balprob=0.12, lyaforest=True, noresample=False, nocolorcuts=False,  
south=True, verbose=False)
```

Build Monte Carlo QSO spectra/templates.

This function generates QSO spectra on-the-fly using PCA decomposition coefficients of SDSS and BOSS QSO spectra. The default is to generate flat, uncorrelated priors on redshift and apparent magnitude (in the bandpass specified by `self.normfilter`).

However, the user also (optionally) has flexibility over the inputs/outputs and can specify any combination of the redshift and output apparent magnitude. Alternatively, the user can pass a complete metadata table, in order to easily regenerate spectra on-the-fly (see the documentation for the `input_meta` argument, below).

Note: The templates are only defined in the range 3500-10000 Å (observed).

Parameters

- `nmodel` (`int`, *optional*) – Number of models to generate (default 100).

- **zrange** (*float, optional*) – Minimum and maximum redshift range. Defaults to a uniform distribution between (0.5, 4.0).
- **magrange** (*float, optional*) – Minimum and maximum magnitude in the bandpass specified by `self.normfilter_south` (if `south=True`) or `self.normfilter_north` (if `south=False`). Defaults to a uniform distribution between (17, 22.7).
- **seed** (*int, optional*) – input seed for the random numbers.
- **redshift** (*float, optional*) – Input/output template redshifts. Array size must equal `nmodel`. Ignores `zrange` input.
- **mag** (*float, optional*) – Input/output template magnitudes in the bandpass specified by `self.normfilter_south` (if `south=True`) or `self.normfilter_north` (if `south=False`). Array size must equal `nmodel`. Ignores `magrange` input.
- **input_meta** (*astropy.Table*) – Input metadata table with the following required columns: SEED, REDSHIFT, MAG, and MAGFILTER (see `desisim.io.empty_metatable` for the expected data types). If present, then all other optional inputs (`nmodel`, `redshift`, `mag`, `zrange`, etc.) are ignored. Note that this argument cannot be used (at this time) to precisely reproduce templates that have had BALs inserted.
- **N_perz** (*int, optional*) – Number of templates per redshift redshift value to generate (default 20).
- **maxiter** (*int*) – maximum number of iterations for finding a non-negative template that also satisfies the color-cuts (default 20).
- **uniform** (*bool, optional*) – Draw uniformly from the PCA coefficients (default False).
- **balprob** (*float, optional*) – Probability that a QSO is a BAL (default 0.12). Only used if `QSO(balqso=True)` at instantiation.
- **lyaforest** (*bool, optional*) – Include Lyman-alpha forest absorption (default True).
- **noresample** (*bool, optional*) – Do not resample the QSO spectra in wavelength (default False).
- **nocolorcuts** (*bool, optional*) – Do not apply the fiducial `rzW1W2` color-cuts (default False).
- **south** (*bool, optional*) – Apply “south” color-cuts using the DECaLS filter system, otherwise apply the “north” (MzLS+BASS) color-cuts. Defaults to True.
- **verbose** (*bool, optional*) – Be verbose!

Returns (outflux, wave, meta, objmeta) tuple where:

- `outflux` (`numpy.ndarray`): Array [`nmodel`, `npix`] of observed-frame spectra ($1e-17$ erg/s/cm²/Å).
- **wave** (`numpy.ndarray`): **Observed-frame wavelength array (Angstrom)**. If `noresample=True` then this is an [`nmodel`, `npix`] array (a different observed-frame array for each object), otherwise it’s a one-dimensional [`npix`]-length array.
- `meta` (`astropy.Table`): Table of meta-data [`nmodel`] for each output spectrum.
- `objmeta` (`astropy.Table`): Additional objtype-specific table data [`nmodel`] for each spectrum.

Raises `ValueError`

```
class desisim.templates.SIMQSO (minwave=3600.0, maxwave=10000.0, cdelt=0.2, wave=None,  
nproc=1, basewave_min=450.0, basewave_max=60000.0,  
basewave_R=8000, normfilter_north='BASS-r',  
normfilter_south='decam2014-r', colorcuts_function=None,  
restframe=False, sqmodel='default')
```

Generate Monte Carlo spectra of quasars (QSOs) using `simqso`.

```
_make_simqso_templates (redshift=None, magrange=None, seed=None, lyaforest=True, nocolor-  
cuts=False, noresample=False, input_qsometa=None, south=True)
```

Wrapper function for actually generating the templates.

```
empty_qsometa (qsometa, nmodel)
```

Initialize an empty `QsoSimPoints` object, which contains all the metadata needed to regenerate `simqso` spectra.

```
make_templates (nmodel=100, zrange=(0.5, 4.0), magrange=(17.0, 22.7), seed=None,  
redshift=None, mag=None, maxiter=20, input_qsometa=None,  
qsometa_extname='QSOMETA', return_qsometa=False, lyaforest=True, no-  
colorcuts=False, noresample=False, south=True, verbose=False)
```

Build Monte Carlo QSO spectra/templates.

- This function generates QSO spectra on-the-fly using @imcgreer's `simqso`. The default is to generate flat, uncorrelated priors on redshift, absolute magnitudes based on the SDSS/DR9 QSO LF, and to compute the corresponding apparent magnitudes using the appropriate per-object K-correction.

Alternatively, the redshift can be input and the absolute and apparent magnitudes will again be computed self-consistently from the QSO LF.

Providing apparent magnitudes on `input` is not supported although it could be if there is need. However, one can control the apparent brightness of the resulting QSO spectra by specifying `magrange`.

- The way the code is currently structured could lead to memory problems if one attempts to generate very large numbers of spectra simultaneously ($>10^4$, perhaps, depending on the machine). However, it can easily be refactored to generate the appropriate number of templates in chunks at the expense of some computational speed.

Parameters

- **nmodel** (*int, optional*) – Number of models to generate (default 100).
- **zrange** (*float, optional*) – Minimum and maximum redshift range. Defaults to a uniform distribution between (0.5, 4.0).
- **magrange** (*float, optional*) – Minimum and maximum magnitude in the bandpass specified by `self.normfilter_south` (if `south=True`) or `self.normfilter_north` (if `south=False`). Defaults to a uniform distribution between (17, 22.7).
- **seed** (*int, optional*) – input seed for the random numbers.
- **redshift** (*float, optional*) – Input/output template redshifts. Array size must equal `nmodel`. Ignores `zrange` input.
- **mag** (*float, optional*) – Not currently supported or used, but see `magrange`. Defaults to `None`.
- **maxiter** (*int*) – maximum number of iterations for finding a template that satisfies the color-cuts (default 20).
- **input_qsometa** (*simqso.sqgrids.QsoSimPoints object or FITS filename*) – Input `QsoSimPoints` object or FITS filename (with a `qsometa_extname` HDU) from which to (re)generate the QSO spectra. All other inputs are ignored when this

optional input is present. Please be cautious when using this argument, as it has not been fully tested.

- **qsometa_extname** (*str*) – FITS extension name to read when input_qsometa is a filename. Defaults to ‘QSOMETA’.
- **return_qsometa** (*bool, optional*) – Return the simqso.sqgrids.QsoSimPoints object, which contains all the data necessary to regenerate the QSO spectra. In particular, the data attribute is an astropy.Table object which contains lots of useful info. This object can be written to disk with the simqso.sqgrids.QsoSimObjects.write method (default False).
- **lyaforest** (*bool, optional*) – Include Lyman-alpha forest absorption (default True).
- **nocolorcuts** (*bool, optional*) – Do not apply the fiducial rzW1W2 color-cuts (default False).
- **noresample** (*bool, optional*) – Do not resample the QSO spectra in wavelength (default False).
- **south** (*bool, optional*) – Apply “south” color-cuts using the DECaLS filter system, otherwise apply the “north” (MzLS+BASS) color-cuts. Defaults to True.
- **verbose** (*bool, optional*) – Be verbose!

Returns (outflux, wave, meta, qsometa) tuple where:

- outflux (numpy.ndarray): Array [nmodel, npix] of observed-frame spectra (1e-17 erg/s/cm²/Å).
- wave (numpy.ndarray): Observed-frame [npix] wavelength array (Angstrom).
- meta (astropy.Table): Table of meta-data [nmodel] for each output spectrum.
- objmeta (astropy.Table): Additional objtype-specific table data [nmodel] for each spectrum.

In addition, if return_qsometa=True then a fourth argument, qsometa, is returned (see the return_qsometa documentation, above).

Raises `ValueError`

class desisim.templates.**STAR** (*minwave=3600.0, maxwave=10000.0, cdelt=0.2, wave=None, baseflux=None, basewave=None, basemeta=None*)

Generate Monte Carlo spectra of generic stars.

make_templates (*nmodel=100, vrad_meansig=(0.0, 200.0), magrange=(18.0, 23.5), seed=None, redshift=None, mag=None, input_meta=None, star_properties=None, south=True, restframe=False, verbose=False*)

Build Monte Carlo spectra/templates for generic stars.

See the SUPERSTAR.make_star_templates function for documentation on the arguments and inherited attributes. Here we only document the arguments which are specific to the STAR class.

Args:

Returns (outflux, wave, meta, objmeta) tuple where:

- outflux (numpy.ndarray): Array [nmodel, npix] of observed-frame spectra (1e-17 erg/s/cm²/Å).
- wave (numpy.ndarray): Observed-frame [npix] wavelength array (Angstrom).
- meta (astropy.Table): Table of meta-data [nmodel] for each output spectrum.

- `objmeta` (`astropy.Table`): Additional objtype-specific table data [`nmodel`] for each spectrum.

Raises:

```
class desisim.templates.STD (minwave=3600.0, maxwave=10000.0, cdelt=0.2, wave=None,  
colorcuts_function=None, normfilter_north='BASS-r',  
normfilter_south='decam2014-r', baseflux=None, basewave=None,  
basemeta=None)
```

Generate Monte Carlo spectra of (metal-poor, main sequence turnoff) standard stars (STD).

```
make_templates (nmodel=100, vrad_meansig=(0.0, 200.0), magrange=(16.0, 19.0), seed=None,  
redshift=None, mag=None, input_meta=None, star_properties=None, nocolor-  
cuts=False, south=True, restframe=False, verbose=False)
```

Build Monte Carlo spectra/templates for STD stars.

See the `SUPERSTAR.make_star_templates` function for documentation on the arguments and inherited attributes. Here we only document the arguments which are specific to the `STD` class.

Args:

Returns (outflux, wave, meta, `objmeta`) tuple where:

- `outflux` (`numpy.ndarray`): Array [`nmodel`, `npix`] of observed-frame spectra (1e-17 erg/s/cm²/Å).
- `wave` (`numpy.ndarray`): Observed-frame [`npix`] wavelength array (Angstrom).
- `meta` (`astropy.Table`): Table of meta-data [`nmodel`] for each output spectrum.
- `objmeta` (`astropy.Table`): Additional objtype-specific table data [`nmodel`] for each spectrum.

Raises:

```
class desisim.templates.SUPERSTAR (objtype='STAR', subtype='', minwave=3600.0,  
maxwave=10000.0, cdelt=0.2, wave=None,  
normfilter_north='BASS-r', normfilter_south='decam2014-  
r', colorcuts_function=None, baseflux=None, base-  
wave=None, basemeta=None)
```

Base class for generating Monte Carlo spectra of the various flavors of stars.

```
make_star_templates (nmodel=100, vrad_meansig=(0.0, 200.0), magrange=(18.0,  
22.0), seed=None, redshift=None, mag=None, input_meta=None,  
star_properties=None, nocolorcuts=False, south=True, restframe=False,  
verbose=False)
```

Build Monte Carlo spectra/templates for various flavors of stars.

This function chooses random subsets of the continuum spectra for the type of star specified by `OBJTYPE`, adds radial velocity jitter, applies the targeting color-cuts, and then normalizes the spectrum to the magnitude in the given filter.

The user also (optionally) has a lot of flexibility over the inputs/outputs and can specify any combination of the radial velocity and apparent magnitude (in the normalization filter specified in the `GALAXY.__init__` method) inputs. Alternatively, the user can pass a complete metadata table, in order to easily regenerate spectra on-the-fly (see the documentation for the `input_meta` argument, below). Finally, the user can pass a `star_properties` table in order to interpolate the base templates to non-gridded values of [Fe/H], `logg`, and `Teff`.

Note:

- The default inputs are generally set to values which are appropriate for generic stars, so be sure to alter them when generating templates for other spectral classes.
 - If both `input_meta` and `star_properties` are passed, then `star_properties` is ignored.
-

Parameters

- **nmodel** (*int, optional*) – Number of models to generate (default 100).
- **vrاد_meansig** (*float, optional*) – Mean and sigma (standard deviation) of the radial velocity “jitter” (in km/s) that should be included in each spectrum. Defaults to a normal distribution with a mean of zero and sigma of 200 km/s.
- **magrange** (*float, optional*) – Minimum and maximum magnitude in the bandpass specified by `self.normfilter_south` (if `south=True`) or `self.normfilter_north` (if `south=False`). Defaults to a uniform distribution between (18, 22).
- **seed** (*int, optional*) – input seed for the random numbers.
- **redshift** (*float, optional*) – Input/output (dimensionless) radial velocity. Array size must equal `nmodel`. Ignores `vrاد_meansig` input.
- **mag** (*float, optional*) – Input/output template magnitudes in the bandpass specified by `self.normfilter_south` (if `south=True`) or `self.normfilter_north` (if `south=False`). Array size must equal `nmodel`. Ignores `magrange` input.
- **input_meta** (*astropy.Table*) – Input metadata table with the following required columns: `TEMPLATEID`, `SEED`, `REDSHIFT`, `MAG`, and `MAGFILTER` (see `desisim.io.empty_metatable` for the expected data types). If present, then all other optional inputs (`nmodel`, `redshift`, `mag`, `zrange`, `vrاد_meansig`, etc.) are ignored.
- **star_properties** (*astropy.Table*) – Input table with the following required columns: `REDSHIFT`, `MAG`, `MAGFILTER`, `TEFF`, `LOGG`, and `FEH` (except for WDs, which don’t need to have an `FEH` column). Optionally, `SEED` can also be included in the table. When this table is passed, the basis templates are interpolated to the desired physical values provided, enabling large numbers of mock stellar spectra to be generated with physically consistent properties. However, be warned that the interpolation scheme is very rudimentary.
- **nocolorcuts** (*bool, optional*) – Do not apply the color-cuts specified by the `self.colorcuts_function` function (default `False`).
- **south** (*bool, optional*) – Apply “south” color-cuts using the DECaLS filter system, otherwise apply the “north” (MzLS+BASS) color-cuts. Defaults to `True`.
- **restframe** (*bool, optional*) – If `True`, return full resolution restframe templates instead of resampled observer frame.
- **verbose** (*bool, optional*) – Be verbose!

Returns (outflux, wave, meta) tuple where:

- `outflux` (`numpy.ndarray`): Array [`nmodel`, `npix`] of observed-frame spectra ($1e-17$ erg/s/cm²/Å).
- `wave` (`numpy.ndarray`): Observed-frame [`npix`] wavelength array (Angstrom).
- `meta` (`astropy.Table`): Table of meta-data [`nmodel`] for each output spectrum.

Raises `ValueError`

```
class desisim.templates.WD (minwave=3600.0, maxwave=10000.0, cdelt=0.2, wave=None, subtype='DA', colorcuts_function=None, normfilter_north='BASS-g', normfilter_south='decam2014-g', baseflux=None, basewave=None, basemeta=None)
```

Generate Monte Carlo spectra of white dwarfs.

make_templates (*nmodel=100, vrad_meansig=(0.0, 200.0), magrange=(16.0, 19.0), seed=None, redshift=None, mag=None, input_meta=None, star_properties=None, nocolorcuts=False, south=True, restframe=False, verbose=False*)

Build Monte Carlo spectra/templates for WD stars.

See the SUPERSTAR.make_star_templates function for documentation on the arguments and inherited attributes. Here we only document the arguments which are specific to the WD class.

Args:

Returns (outflux, wave, meta, objmeta) tuple where:

- outflux (numpy.ndarray): Array [nmodel, npix] of observed-frame spectra (1e-17 erg/s/cm²/Å).
- wave (numpy.ndarray): Observed-frame [npix] wavelength array (Angstrom).
- meta (astropy.Table): Table of meta-data [nmodel] for each output spectrum.
- objmeta (astropy.Table): Additional objtype-specific table data [nmodel] for each spectrum.

Raises `ValueError` – If the INPUT_META or STAR_PROPERTIES table contains different values of SUBTYPE.

`desisim.templates.specify_galparams_dict` (*templatetype, zrange=None, magrange=None, oiiihrange=None, logvdisp_meansig=None, minlineflux=None, trans_rfluxratorange=None, redshift=None, mag=None, vdisp=None, nocolorcuts=None, nocontinuum=None, agnlike=None, novdisp=None, restframe=None*)

Creates a dictionary of keyword variables to be passed to GALAXY.make_templates (or one of GALAXY's child classes). Allows the user to fully define the templated spectra, via defining individual targets or ranges in values. Values already specified in get_targets are not included here. Anything not define or set to None will not be assigned and CLASS.make_templates will assume the following as defaults:

- nmodel=100, zrange=(0.6, 1.6), magrange=(21.0, 23.5),
- oiiihrange=(-0.5, 0.2), logvdisp_meansig=(1.9, 0.15),
- minlineflux=0.0, trans_rfluxratorange=(0.01, 0.1),
- seed=None, redshift=None, mag=None, vdisp=None,
- input_meta=None, nocolorcuts=False, nocontinuum=False,
- agnlike=False, novdisp=False, restframe=False, verbose=False

Parameters

- **nmodel** (*) – Number of models to generate (default 100).
- **zrange** (*) – Minimum and maximum redshift range. Defaults to a uniform distribution between (0.6, 1.6).
- **magrange** (*) – Minimum and maximum magnitude in the bandpass specified by self.normfilter. Defaults to a uniform distribution between (21, 23.4) in the r-band.
- **oiiihrange** (*) – Minimum and maximum logarithmic [OIII] 5007/H-beta line-ratio. Defaults to a uniform distribution between (-0.5, 0.2).
- **logvdisp_meansig** (*) – Logarithmic mean and sigma values for the (Gaussian) stellar velocity dispersion distribution. Defaults to log10-sigma=1.9+/-0.15 km/s.
- **minlineflux** (*) – Minimum emission-line flux in the line specified by self.normline (default 0 erg/s/cm²).

- **trans_rfluxratio** (*) – r-band flux ratio of the SNIa spectrum with respect to the underlying galaxy. Defaults to a uniform distribution between (0.01, 0.1).
- **seed** (*) – Input seed for the random numbers.
- **redshift** (*) – Input/output template redshifts. Array size must equal nmodel. Ignores zrange input.
- **mag** (*) – Input/output template magnitudes in the band specified by self.normfilter. Array size must equal nmodel. Ignores magrange input.
- **vdisp** (*) – Input/output velocity dispersions. Array size must equal nmodel. Ignores magrange input.
- **input_meta** (*) – *Input* metadata table with the following required columns: TEMPLATEID, SEED, REDSHIFT, VDISP, MAG (where mag is specified by self.normfilter). In addition, if transient is True then the table must also contain SNE_TEMPLATEID, SNE_EPOCH, and SNE_RFLUXRATIO columns. See `desisim.io.empty_metatable` for the required data type for each column. If this table is passed then all other optional inputs (nmodel, redshift, vdisp, mag, zrange, logvdisp_meansig, etc.) are ignored.
- **nocolorcuts** (*) – Do not apply the color-cuts specified by the self.colorcuts_function function (default False).
- **nocontinuum** (*) – Do not include the stellar continuum in the output spectrum (useful for testing; default False). Note that this option automatically sets nocolorcuts to True and transient to False.
- **novdisp** (*) – Do not velocity-blur the spectrum (default False).
- **agnlike** (*) – Adopt AGN-like emission-line ratios (e.g., for the LRGs and some BGS galaxies) (default False, meaning we adopt star-formation-like line-ratios). Option not yet supported.
- **restframe** (*) – If True, return full resolution restframe templates instead of resampled observer frame.
- **verbose** (*) – Be verbose!

Returns

dictionary containing all of the values passed defined with variable names as the corresponding key. These are intentionally identical to those passed to the `make_templates` classes above

Return type

- `fulldef_dict` (dict)

`desisim.templates.specify_starparams_dict` (*templatetype*, *vrad_meansig=None*, *magrange=None*, *redshift=None*, *mag=None*, *input_meta=None*, *star_properties=None*, *nocolorcuts=None*, *restframe=None*)

Creates a dictionary of keyword variables to be passed to `SUPERSTAR.make_templates` (or one of `SUPERSTAR`'s child classes). Allows the user to fully define the templated spectra, via defining individual targets or ranges in values. Values already specified in `get_targets` are not included here. Anything not define or set to None will not be assigned and `CLASS.make_templates` will assume the following as defaults:

- `nmodel=100`, `vrad_meansig=(0.0, 200.0)`,
- `magrange=(18.0, 23.5)`, `seed=None`, `redshift=None`,
- `mag=None`, `input_meta=None`, `star_properties=None`,

- `nocolorcuts=False`, `restframe=False`, `verbose=False`

Parameters

- **nmodel** (*) – Number of models to generate (default 100).
- **vrاد_meansig** (*) – Mean and sigma (standard deviation) of the radial velocity “jitter” (in km/s) that should be included in each spectrum. Defaults to a normal distribution with a mean of zero and sigma of 200 km/s.
- **magrange** (*) – Minimum and maximum magnitude in the bandpass specified by `self.normfilter`. Defaults to a uniform distribution between (18, 23.5) in the r-band.
- **seed** (*) – input seed for the random numbers.
- **redshift** (*) – Input/output (dimensionless) radial velocity. Array size must equal `nmodel`. Ignores `vrاد_meansig` input.
- **mag** (*) – Input/output template magnitudes in the band specified by `self.normfilter`. Array size must equal `nmodel`. Ignores `magrange` input.
- **input_meta** (*) – *Input* metadata table with the following required columns: `TEMPLATEID`, `SEED`, `REDSHIFT`, and `MAG` (where `mag` is specified by `self.normfilter`). See `desisim.io.empty_metatable` for the required data type for each column. If this table is passed then all other optional inputs (`nmodel`, `redshift`, `mag`, `vrاد_meansig` etc.) are ignored.
- **star_properties** (*) – *Input* table with the following required columns: `REDSHIFT`, `MAG`, `TEFF`, `LOGG`, and `FEH` (except for WDs, which don’t need to have an `FEH` column). Optionally, `SEED` can also be included in the table. When this table is passed, the basis templates are interpolated to the desired physical values provided, enabling large numbers of mock stellar spectra to be generated with physically consistent properties.
- **nocolorcuts** (*) – Do not apply the color-cuts specified by the `self.colorcuts_function` function (default `False`).
- **restframe** (*) – If `True`, return full resolution restframe templates instead of resampled observer frame.
- **verbose** (*) – Be verbose!

Returns

dictionary containing all of the values passed defined with variable names as the corresponding key. These are intentionally identical to those passed to the `make_templates` classes above

Return type

- `fulldef_dict` (dict)

2.3.27 desisim.util

Utility functions for `desisim`. These may belong elsewhere?

`desisim.util.dateobs2night` (*dateobs*)

Convert UTC `dateobs` to KPNO YEARMMDD night string

Parameters `dateobs` – float -> interpret as MJD str -> interpret as ISO 8601 YEAR-MM-DDThh:mm:ss.s string `astropy.time.Time` -> UTC `python datetime.datetime` -> UTC

TODO: consider adding format option to pass to astropy.time.Time without otherwise questioning the dateobs format

`desisim.util.medxbin(x, y, binsize, minpts=20, xmin=None, xmax=None)`

Compute the median (and other statistics) in fixed bins along the x-axis.

`desisim.util.spline_medfilt2d(image, kernel_size=201)`

Returns a 2D spline interpolation of a median filtered input image

CHAPTER 3

Indices and tables

- `genindex`
- `modindex`
- `search`

d

- desisim, 13
- desisim.archetypes, 13
- desisim.bal, 14
- desisim.batch, 15
- desisim.cosmology, 15
- desisim.dla, 15
- desisim.eboss, 17
- desisim.io, 18
- desisim.lya_mock_pld, 22
- desisim.lya_spectra, 23
- desisim.pixelsplines, 25
- desisim.qso_template, 26
- desisim.qso_template.desi_qso_templ, 26
- desisim.qso_template.fit_boss_qsos, 27
- desisim.qso_template.qso_pca, 27
- desisim.qso_template.tests, 28
- desisim.quickcat, 28
- desisim.quicksurvey, 30
- desisim.scripts, 31
- desisim.scripts.qa_s2n, 31
- desisim.scripts.qa_zfind, 31
- desisim.spec_qa, 31
- desisim.spec_qa.high_level, 32
- desisim.spec_qa.redshifts, 32
- desisim.spec_qa.s2n, 35
- desisim.spec_qa.utils, 36
- desisim.specsim, 36
- desisim.targets, 36
- desisim.templates, 38
- desisim.util, 52

Symbols

- `_blurmatrix()` (*desisim.templates.GALAXY method*), 41
- `_default_wave()` (*in module desisim.targets*), 37
- `_make_simqso_templates()` (*desisim.templates.SIMQSO method*), 46
- `_parse_filename()` (*in module desisim.io*), 19
- `_qso_format_version()` (*in module desisim.io*), 19
- `_resize()` (*in module desisim.io*), 19
- `_sample_pcacoeff()` (*desisim.templates.QSO method*), 44
- ### A
- `add_camera()` (*desisim.io.SimSpec method*), 19
- `apply_lya_transmission()` (*in module desisim.lya_spectra*), 23
- `apply_metals_transmission()` (*in module desisim.lya_spectra*), 23
- ArcheTypes (*class in desisim.archetypes*), 13
- ### B
- `backup_epoch_data()` (*desisim.quicksurvey.SimSetup method*), 30
- BAL (*class in desisim.bal*), 14
- BGS (*class in desisim.templates*), 38
- ### C
- `calc_dz()` (*in module desisim.spec_qa.redshifts*), 32
- `calc_dzsig()` (*in module desisim.spec_qa.redshifts*), 32
- `calc_lz()` (*in module desisim.dla*), 15
- `calc_nodes()` (*in module desisim.batch*), 15
- `calc_obj_stats()` (*in module desisim.spec_qa.redshifts*), 32
- `calculate_lox()` (*in module desisim.dla*), 15
- `catastrophic_dv()` (*in module desisim.spec_qa.utils*), 36
- `cen2bound()` (*in module desisim.pixelsplines*), 25
- `chk_desi_qso_templates()` (*in module desisim.qso_template.desi_qso_tmpl*), 26
- `cleanup_directories()` (*desisim.quicksurvey.SimSetup method*), 31
- `compute_chi2()` (*in module desisim.archetypes*), 14
- `compute_duck_slopes()` (*in module desisim.pixelsplines*), 25
- `create_directories()` (*desisim.quicksurvey.SimSetup method*), 31
- `create_sdss2desi_redshift_distribution_ratio()` (*in module desisim.eboss*), 17
- `create_sdss_footprint()` (*in module desisim.eboss*), 18
- `create_surveyfile()` (*desisim.quicksurvey.SimSetup method*), 31
- `criteria()` (*in module desisim.spec_qa.redshifts*), 32
- ### D
- `dateobs2night()` (*in module desisim.util*), 52
- DESI_BASIS_TEMPLATES, 11
- `desi_qso_templates()` (*in module desisim.qso_template.desi_qso_tmpl*), 26
- desisim (*module*), 13
- desisim.archetypes (*module*), 13
- desisim.bal (*module*), 14
- desisim.batch (*module*), 15
- desisim.cosmology (*module*), 15
- desisim.dla (*module*), 15
- desisim.eboss (*module*), 17
- desisim.io (*module*), 18
- desisim.lya_mock_p1d (*module*), 22
- desisim.lya_spectra (*module*), 23
- desisim.pixelsplines (*module*), 25
- desisim.qso_template (*module*), 26
- desisim.qso_template.desi_qso_tmpl (*module*), 26
- desisim.qso_template.fit_boss_qsos (*module*), 27
- desisim.qso_template.qso_pca (*module*), 27
- desisim.qso_template.tests (*module*), 28

desisim.quickcat (*module*), 28
 desisim.quicksurvey (*module*), 30
 desisim.scripts (*module*), 31
 desisim.scripts.qa_s2n (*module*), 31
 desisim.scripts.qa_zfind (*module*), 31
 desisim.spec_qa (*module*), 31
 desisim.spec_qa.high_level (*module*), 32
 desisim.spec_qa.redshifts (*module*), 32
 desisim.spec_qa.s2n (*module*), 35
 desisim.spec_qa.utils (*module*), 36
 desisim.specsim (*module*), 36
 desisim.targets (*module*), 36
 desisim.templates (*module*), 38
 desisim.util (*module*), 52
 dla_spec () (*in module desisim.dla*), 15
 do_boss_lya_parallel () (*in module desisim.qso_template.fit_boss_qsos*), 27
 do_boss_lya_parallel () (*in module desisim.qso_template.qso_pca*), 28
 do_sdss_lya_parallel () (*in module desisim.qso_template.fit_boss_qsos*), 27
 dz_summ () (*in module desisim.spec_qa.redshifts*), 32

E

ELG (*class in desisim.templates*), 38
 elg_flux_lim () (*in module desisim.spec_qa.utils*), 36
 empty_balmeta () (*desisim.bal.BAL method*), 14
 empty_metatable () (*in module desisim.io*), 19
 empty_qsometa () (*desisim.templates.SIMQSO method*), 46
 empty_snetatable () (*in module desisim.io*), 20
 EMSpectrum (*class in desisim.templates*), 39
 environment variable
 DESI_BASIS_TEMPLATES, 11
 epoch_data_exists () (*desisim.quicksurvey.SimSetup method*), 31
 epochs_path (*desisim.quicksurvey.SimSetup attribute*), 30
 evaluate_fN () (*in module desisim.dla*), 16

F

failed_parallel () (*in module desisim.qso_template.fit_boss_qsos*), 27
 fiberassign (*desisim.quicksurvey.SimSetup attribute*), 30
 fibers2cameras () (*in module desisim.io*), 20
 fig_desi_tmpl_z_i () (*in module desisim.qso_template.desi_qso_tmpl*), 27
 find_basis_template () (*in module desisim.io*), 20
 find_cosmics () (*in module desisim.io*), 20
 findfile () (*in module desisim.io*), 20

fit_eigen () (*in module desisim.qso_template.fit_boss_qsos*), 27
 fit_eigen () (*in module desisim.qso_template.qso_pca*), 28
 FootprintEBOSS (*class in desisim.eboss*), 17
 forbidmog (*desisim.templates.EMSpectrum attribute*), 40

G

GALAXY (*class in desisim.templates*), 41
 gauss_blur_matrix () (*in module desisim.pixelsplines*), 25
 get_archetypes () (*desisim.archetypes.ArcheTypes method*), 13
 get_density () (*desisim.lya_mock_p1d.MockMaker method*), 22
 get_gaussian_fields () (*desisim.lya_mock_p1d.MockMaker method*), 23
 get_lya_skewers () (*desisim.lya_mock_p1d.MockMaker method*), 23
 get_median_obsconditions () (*in module desisim.quickcat*), 28
 get_meta () (*in module desisim.spec_qa.high_level*), 32
 get_observed_redshifts () (*in module desisim.quickcat*), 28
 get_redshift_efficiency () (*in module desisim.quickcat*), 29
 get_redshifts () (*desisim.lya_mock_p1d.MockMaker method*), 23
 get_simtype () (*in module desisim.targets*), 37
 get_simulator () (*in module desisim.specsim*), 36
 get_spectra () (*in module desisim.lya_spectra*), 24
 get_sty_otype () (*in module desisim.spec_qa.utils*), 36
 get_targets () (*in module desisim.targets*), 37
 get_targets_parallel () (*in module desisim.targets*), 37
 get_tau () (*in module desisim.lya_mock_p1d*), 23
 get_tile_radec () (*in module desisim.io*), 20
 get_zeff_obs () (*in module desisim.quickcat*), 29

I

init_fNHI () (*in module desisim.dla*), 16
 insert_bals () (*desisim.bal.BAL method*), 14
 insert_dlas () (*in module desisim.dla*), 16

L

line (*desisim.templates.EMSpectrum attribute*), 40
 lineratios () (*desisim.templates.GALAXY method*), 41

load_all_s2n_values() (in module *desisim.spec_qa.s2n*), 35
 load_s2n_values() (in module *desisim.spec_qa.s2n*), 35
 load_simspec_summary() (in module *desisim.io*), 21
 load_z() (in module *desisim.spec_qa.redshifts*), 33
 log10wave (*desisim.templates.EMSpectrum* attribute), 40
 LRG (class in *desisim.templates*), 43

M

main() (in module *desisim.spec_qa.high_level*), 32
 make_galaxy_templates() (*desisim.templates.GALAXY* method), 41
 make_star_templates() (*desisim.templates.SUPERSTAR* method), 48
 make_templates() (*desisim.templates.BGS* method), 38
 make_templates() (*desisim.templates.ELG* method), 39
 make_templates() (*desisim.templates.LRG* method), 43
 make_templates() (*desisim.templates.MWS_STAR* method), 44
 make_templates() (*desisim.templates.QSO* method), 44
 make_templates() (*desisim.templates.SIMQSO* method), 46
 make_templates() (*desisim.templates.STAR* method), 47
 make_templates() (*desisim.templates.STD* method), 48
 make_templates() (*desisim.templates.WD* method), 49
 match_otype() (in module *desisim.spec_qa.utils*), 36
 match_truth_z() (in module *desisim.spec_qa.redshifts*), 33
 mean_tmpl_zi() (in module *desisim.qso_template.desi_qso_tmpl*), 27
 medxbin() (in module *desisim.util*), 53
 MockMaker (class in *desisim.lya_mock_p1d*), 22
 MWS_STAR (class in *desisim.templates*), 44

N

n_epochs (*desisim.quicksurvey.SimSetup* attribute), 30
 niidoublet (*desisim.templates.EMSpectrum* attribute), 40

O

obj_fig() (in module *desisim.spec_qa.redshifts*), 33
 obj_requirements() (in module *desisim.spec_qa.redshifts*), 33
 obj_s2n_wave() (in module *desisim.spec_qa.s2n*), 36

obj_s2n_z() (in module *desisim.spec_qa.s2n*), 36
 oiiidoublet (*desisim.templates.EMSpectrum* attribute), 40
 output_path (*desisim.quicksurvey.SimSetup* attribute), 30

P

parse_s2n_values() (in module *desisim.spec_qa.s2n*), 36
 PixelSpline (class in *desisim.pixelsplines*), 25
 PixSplineError, 25
 plot_slices() (in module *desisim.spec_qa.redshifts*), 33
 point_evaluate() (*desisim.pixelsplines.PixelSpline* method), 25
 power_amplitude() (in module *desisim.lya_mock_p1d*), 23
 power_kms() (in module *desisim.lya_mock_p1d*), 23

Q

QSO (class in *desisim.templates*), 44
 quickcat() (in module *desisim.quickcat*), 29

R

read_basis_templates() (in module *desisim.io*), 21
 read_cosmics() (in module *desisim.io*), 21
 read_lya_skewers() (in module *desisim.lya_spectra*), 24
 read_qso_eigen() (in module *desisim.qso_template.fit_boss_qsos*), 27
 read_qso_eigen() (in module *desisim.qso_template.qso_pca*), 28
 read_sdss_redshift_distribution() (*desisim.eboss.RedshiftDistributionEBOSS* static method), 17
 read_simspec() (in module *desisim.io*), 22
 redshift_fraction() (*desisim.eboss.RedshiftDistributionEBOSS* method), 17
 RedshiftDistributionEBOSS (class in *desisim.eboss*), 17
 repack_coeff() (in module *desisim.qso_template.desi_qso_tmpl*), 27
 resample() (*desisim.pixelsplines.PixelSpline* method), 25
 responsibility() (*desisim.archetypes.ArcheTypes* method), 14
 reverse_dictionary() (in module *desisim.quickcat*), 30

S

sample_nz() (in module *desisim.targets*), 37

`sample_objtype()` (in module `desisim.targets`), 37
`sdss_subsample()` (in module `desisim.eboss`), 18
`sdss_subsample_redshift()` (in module `desisim.eboss`), 18
`simdir()` (in module `desisim.io`), 22
`SIMQSO` (class in `desisim.templates`), 45
`SimSetup` (class in `desisim.quicksurvey`), 30
`SimSpec` (class in `desisim.io`), 19
`SimSpecCamera` (class in `desisim.io`), 19
`simulate()` (`desisim.quicksurvey.SimSetup` method), 31
`simulate_epoch()` (`desisim.quicksurvey.SimSetup` method), 31
`slice_simz()` (in module `desisim.spec_qa.redshifts`), 34
`specify_galparams_dict()` (in module `desisim.templates`), 50
`specify_starparams_dict()` (in module `desisim.templates`), 51
`spectrum()` (`desisim.templates.EMSpectrum` method), 40
`spectype_confusion()` (in module `desisim.spec_qa.redshifts`), 34
`splice_fits()` (in module `desisim.qso_template.fit_boss_qsos`), 27
`spline_medfilt2d()` (in module `desisim.util`), 53
`STAR` (class in `desisim.templates`), 47
`STD` (class in `desisim.templates`), 48
`summ_fig()` (in module `desisim.spec_qa.redshifts`), 34
`summ_stats()` (in module `desisim.spec_qa.redshifts`), 35
`SUPERSTAR` (class in `desisim.templates`), 48

T

`targets_path` (`desisim.quicksurvey.SimSetup` attribute), 30
`template_balmeta()` (`desisim.bal.BAL` method), 15
`template_fiberassign` (`desisim.quicksurvey.SimSetup` attribute), 30
`tst_random_set()` (in module `desisim.qso_template.desi_qso_tmpl`), 27

U

`update_observed_tiles()` (`desisim.quicksurvey.SimSetup` method), 31

V

`voigt_tau()` (in module `desisim.dla`), 16
`voigt_wofz()` (in module `desisim.dla`), 16

W

`WD` (class in `desisim.templates`), 49
`WeightedRebinCoadder` (class in `desisim.pixelsplines`), 25

`write_simpix()` (in module `desisim.io`), 22
`write_simspec()` (in module `desisim.io`), 22
`write_simspec_arc()` (in module `desisim.io`), 22

Z

`zstats()` (in module `desisim.spec_qa.redshifts`), 35